

MINI SERIES

Various options for 3mm, 4mm,
5mm, 6mm width

Single color, CCT and RGB
available

Applied to LGP and slim profile etc.




MINI SERIES-3MM



MN-2016A-182-24



Color Available



IP Rating	IP22(N)	IP64(WP)	IP65(WS)	IP67(WT)	IP67(WHE)	IP68(WE)	IP68(WTS/WTU)
Graphical							
PCB Width(mm)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DC 24V 5 yrs warranty

Optical & Electrical Parameters

Model No.	Voltage(V DC)	Light Color	CCT(K)	Ra	Luminous Flux(lm/m)	Efficacy(lm/W)	Power(W/m)
MN-2016A-182-24	24	W	4000	90+	908	97	9.36


Other Parameters

Model No.	LED QTY(pcs/m)	Standad Run(m/inch)	Min Cuttable Length(mm/inch)	Standard Packing Size/Reel L*W(mm/inch)
MN-2016A-182-24	182	3.0 [118.11]	38.46 [1.51]	5000X3.0 [196.85X0.12]

Profile Drawings

Length Unit : mm/inch

MN-2016A-182-24



Aluminum Profile



SL080805-A


MINI SERIES-4MM



MN-2110-238-24



Color Available



IP Rating	IP22(N)	IP64(WP)	IP65(WS)	IP67(WT)	IP67(WHE)	IP68(WE)	IP68(WTS/WTU)
Graphical							
PCB Width(mm)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

DC 24V 5 yrs warranty

Optical & Electrical Parameters


Model No.	Voltage(V DC)	Light Color	CCT(K)	Ra	Luminous Flux(lm/m)	Efficacy(lm/W)	Power(W/m)
MN-2110-238-24	24	W	4000	90/95+	1126/1032	92/84	12.24

Other Parameters

Model No.	LED QTY(pcs/m)	Max Run(m/inch)	Min Cuttable Length(mm/inch)	Standard Packing Size/Reel L*W(mm/inch)
MN-2110-238-24	238	2.0[78.74]	29.4[1.16]	5000X4 [196.85X0.16]

Profile Drawings

Length Unit : mm/inch



Aluminum Profile



SL080805-A



SL080804-A



SL161508-A



SL101508-A


MINI SERIES-4MM



MN-2835A-120-12/24



Color Available



DC 12/24V 5 yrs warranty



Optical & Electrical Parameters

Model No.	Voltage(V DC)	Light Color	CCT(K)	Ra	Luminous Flux(lm/m)	Efficacy(lm/W)	Power(W/m)
MN-2835A-120-12/24	12/24	W	4000	80+	960	100	9.6

Other Parameters

Model No.	LED QTY(pcs/m)	Max Run(m/inch)	Min Cuttable Length (mm/inch)	Standard Packing Size/Reel L*W(mm/inch)
MN-2835A-120-12/24	120	1.5[59.05]/3.0[118.11]	25.0 [1.00]/50.0[1.97]	5000X4[196.85X0.16]

Profile Drawings

Length Unit : mm/inch

MN-2835A-120-12



MN-2835A-120-24



Aluminum Profile



SL080805-A

MINI SERIES-5MM



MN-2835A-60-12/24



Color Available



DC 12/24V 5 yrs warranty



Optical & Electrical Parameters

Model No.	Voltage(V DC)	Light Color	CCT(K)	Ra	Luminous Flux(lm/m)	Efficacy(lm/W)	Power(W/m)
MN-2835A-60-12/24	12/24	W	6500	80+	456	95	4.8


Other Parameters

Model No.	LED QTY(pcs/m)	Max Run(m/inch)	Min Cuttable Length(mm/inch)	Standard Packing Size/Reel L*W(mm/inch)
MN-2835A-60-12/24	60	3.0 [118.11]/5.0 [196.85]	50.0 [1.97]/100.0 [3.94]	5000X5 [196.85X0.20]


Profile Drawings

Length Unit : mm/inch

MN-2835A-60-12



MN-2835A-60-24



Aluminum Profile



SL080805-A

