



FEATURES

- "F-connect" design for heatsink and optics.
- Low profile.
- Fit in most of MR16 LED downlight converters.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	-
Output Voltage/Current	DC36V/440mA
Power	15.8W
Rated Input Current	-
THD	-
PF value	-
Ingress Protection	IP65
Operating Temperature	-10—40°C
L70/B50 at 25°C	>105000H
L90/B10 at 25°C	>105000H

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	> 90
SDCM	< 3
Beam Angle	15°/25°/38°/60°
Colour Temperature	2700K/3000K/4000K
System luminous efficacy up to	101lm/W

Packaging

Box Dimensions	L78 x W78 x H78 mm
Box Net Weight	0.218Kg
Box Gross Weight	0.242Kg
Carton Dimensions	L402 x W402 x H102 mm/25 PCS
Carton Net Weight	6.05Kg
Carton Gross Weight	7.55Kg



CCT		Beam Angle	Lumen	Efficacy
2700K	CRI 90+	15°	1781lm	99lm/W
		25°	1723lm	96lm/W
		38°	1687lm	94lm/W
		60°	1659lm	93lm/W
3000K		15°	1820lm	101lm/W
		25°	1740lm	98lm/W
		38°	1707lm	96lm/W
		60°	1688lm	95lm/W
4000K		15°	1780lm	100lm/W
		25°	1759lm	98lm/W
		38°	1729lm	97lm/W
		60°	1706lm	95lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS