



FEATURES

- "F-connect" design for heatsink and optics.
- Low profile.
- Fit in most of MR16 LED downlight converters.
- 5-year guarantee.

Technical Data

| | |
|------------------------|-------------|
| Input Voltage/Hz | - |
| Output Voltage/Current | DC36V/440mA |
| Power | 15.8W |
| Rated Input Current | - |
| THD | - |
| PF value | - |
| Ingress Protection | IP65 |
| Operating Temperature | -10—40°C |
| L70/B50 at 25°C | >105000H |
| L90/B10 at 25°C | >105000H |

LED and Optical Data

| | |
|--------------------------------|-------------------|
| LED Brand | Bridgelux COB LED |
| CRI | >90 |
| SDCM | <3 |
| Beam Angle | 15°/25°/38°/60° |
| Colour Temperature | 2700K/3000K/4000K |
| System luminous efficacy up to | 101lm/W |

Packaging

| | |
|---------------------|------------------------------|
| Box Dimensions | L78 x W78 x H78 mm |
| Box Net Weight | 0.218Kg |
| Box Gross Weight | 0.242Kg |
| Carton Dimensions | L402 x W402 x H102 mm/25 PCS |
| Carton Net Weight | 6.05Kg |
| Carton Gross Weight | 7.55Kg |



| CCT | | Beam Angle | Lumen | Efficacy |
|-------|---------|------------|--------|----------|
| 2700K | CRI 90+ | 15° | 1781lm | 99lm/W |
| | | 25° | 1723lm | 96lm/W |
| | | 38° | 1687lm | 94lm/W |
| | | 60° | 1659lm | 93lm/W |
| 3000K | | 15° | 1820lm | 101lm/W |
| | | 25° | 1740lm | 98lm/W |
| | | 38° | 1707lm | 96lm/W |
| | | 60° | 1688lm | 95lm/W |
| 4000K | | 15° | 1780lm | 100lm/W |
| | | 25° | 1759lm | 98lm/W |
| | | 38° | 1729lm | 97lm/W |
| | | 60° | 1706lm | 95lm/W |

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS