



Cut-out: Ø100mm

FEATURES

- Modular Design.
- System power up to 20W.
- Interchangeable beam.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/350mA
Power	14.5W
Rated Input Current	0.0725A
PF value	>0.9
THD	<6%
Ingress Protection	IP54
Operating Temperature	-10—40℃
Dimmability	Non-dimmable with PHILIPS driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperature	2700k/3000K/4000K
System luminous efficacy up to	98lm/W

Packaging

Box Dimensions	L165 x W145 x H133mm
Box Net Weight	0.70Kg
Box Gross Weight	0.82Kg
Carton Dimensions	L450 x W345 x H555 mm/24 PCS
Carton Net Weight	16.8Kg
Carton Gross Weight	20.48Kg



Model	CCT	Beam Angle	Lumen	Efficacy
DL51-15-XX-01	2700K	15°	1249lm	88.6lm/W
		24°	1256lm	89lm/W
		36°	1248lm	88.4lm/W
		60°	1257lm	89lm/W
DL51-15-XX-01	3000K	15°	1290lm	90.6lm/W
		24°	1301lm	91.5lm/W
		36°	1285lm	90.5lm/W
		60°	1306lm	91.8lm/W
DL51-15-XX-01	4000K	15°	1369lm	97.5lm/W
		24°	1379lm	98lm/W
		36°	1336lm	95.2lm/W
		60°	1359lm	96.7lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS