



Indoor Luminaire Photometric Data

Description Information

Luminary Name: DL43-05-PR-03 RA90 4000K 15D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2020/12/25
Manufacture: Shenzhen Norming Lighting Co.Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.000m*0.000m*0.000m		Lum. Area (m2):0.000	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 213.380	Luminary Flux(lm): 213.384	Field Angle(10%Imax): 41.0(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 213.384lm 100.00%	
Rated Voltage(V):	Luminary EER(lm/W): 45.391	Up Lumens&Percent: 0.000lm 0.00%	
Tested Power(W): 4.701	Max. Candela(cd): 1083.511	S/MH: C0_a180=0.419 C90_270=0.397	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=2.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.3, 0.021, 0.912	Beam Angle(50%Imax): 23.9(°)	ErP ϕ use(90°): 206.913lm	
Lamp Size(W*L*H):0.000m*0.000m*0.000m	Left=-9.9°, Right=14.0°	IRF(%): 944.905	



2D Plane Light Intensity Distribution Curve


Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Deparment
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



3D Light Intensity Distribution Modal

Lum. Name:DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Deparment
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2020/12/25

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:DL43-05-PR-01 RA90 4000K 15D.IES

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.99	0.99	0.46	0.46	47.0-48.0	0.44	208.69	0.21	97.80
1.0-2.0	2.93	3.92	1.38	1.84	48.0-49.0	0.42	209.11	0.20	98.00
2.0-3.0	4.79	8.71	2.25	4.08	49.0-50.0	0.40	209.52	0.19	98.19
3.0-4.0	6.50	15.22	3.05	7.13	50.0-51.0	0.38	209.90	0.18	98.37
4.0-5.0	8.04	23.25	3.77	10.90	51.0-52.0	0.36	210.26	0.17	98.54
5.0-6.0	9.38	32.63	4.40	15.29	52.0-53.0	0.34	210.60	0.16	98.70
6.0-7.0	10.51	43.14	4.93	20.22	53.0-54.0	0.32	210.92	0.15	98.85
7.0-8.0	11.39	54.54	5.34	25.56	54.0-55.0	0.30	211.22	0.14	98.99
8.0-9.0	12.00	66.54	5.63	31.19	55.0-56.0	0.28	211.50	0.13	99.12
9.0-10.0	12.33	78.87	5.78	36.96	56.0-57.0	0.25	211.75	0.12	99.24
10.0-11.0	12.39	91.26	5.81	42.77	57.0-58.0	0.23	211.98	0.11	99.35
11.0-12.0	12.18	103.44	5.71	48.48	58.0-59.0	0.21	212.20	0.10	99.45
12.0-13.0	11.72	115.17	5.49	53.97	59.0-60.0	0.19	212.39	0.09	99.54
13.0-14.0	11.06	126.23	5.18	59.16	60.0-61.0	0.17	212.57	0.08	99.62
14.0-15.0	10.24	136.46	4.80	63.95	61.0-62.0	0.15	212.72	0.07	99.69
15.0-16.0	9.29	145.75	4.36	68.31	62.0-63.0	0.14	212.86	0.06	99.76
16.0-17.0	8.28	154.03	3.88	72.19	63.0-64.0	0.12	212.97	0.05	99.81
17.0-18.0	7.23	161.26	3.39	75.57	64.0-65.0	0.10	213.07	0.05	99.86
18.0-19.0	6.21	167.46	2.91	78.48	65.0-66.0	0.08	213.15	0.04	99.89
19.0-20.0	5.26	172.72	2.46	80.94	66.0-67.0	0.06	213.21	0.03	99.92
20.0-21.0	4.42	177.14	2.07	83.01	67.0-68.0	0.05	213.26	0.02	99.95
21.0-22.0	3.70	180.83	1.73	84.75	68.0-69.0	0.04	213.30	0.02	99.96
22.0-23.0	3.10	183.93	1.45	86.20	69.0-70.0	0.03	213.34	0.01	99.98
23.0-24.0	2.62	186.55	1.23	87.43	70.0-71.0	0.02	213.36	0.01	99.99
24.0-25.0	2.24	188.79	1.05	88.48	71.0-72.0	0.01	213.37	0.01	100.00
25.0-26.0	1.94	190.73	0.91	89.38	72.0-73.0	0.01	213.38	0.00	100.00
26.0-27.0	1.70	192.43	0.80	90.18	73.0-74.0	0.00	213.38	0.00	100.00
27.0-28.0	1.52	193.94	0.71	90.89	74.0-75.0	0.00	213.38	0.00	100.00
28.0-29.0	1.37	195.31	0.64	91.53	75.0-76.0	0.00	213.38	0.00	100.00
29.0-30.0	1.25	196.56	0.58	92.12	76.0-77.0	0.00	213.38	0.00	100.00
30.0-31.0	1.14	197.70	0.53	92.65	77.0-78.0	0.00	213.38	0.00	100.00
31.0-32.0	1.05	198.75	0.49	93.14	78.0-79.0	0.00	213.38	0.00	100.00
32.0-33.0	0.96	199.71	0.45	93.59	79.0-80.0	0.00	213.38	0.00	100.00
33.0-34.0	0.88	200.59	0.41	94.01	80.0-81.0	0.00	213.38	0.00	100.00
34.0-35.0	0.81	201.41	0.38	94.39	81.0-82.0	0.00	213.38	0.00	100.00
35.0-36.0	0.75	202.16	0.35	94.74	82.0-83.0	0.00	213.38	0.00	100.00
36.0-37.0	0.70	202.86	0.33	95.07	83.0-84.0	0.00	213.38	0.00	100.00
37.0-38.0	0.65	203.51	0.31	95.37	84.0-85.0	0.00	213.38	0.00	100.00
38.0-39.0	0.62	204.13	0.29	95.66	85.0-86.0	0.00	213.38	0.00	100.00
39.0-40.0	0.58	204.71	0.27	95.94	86.0-87.0	0.00	213.38	0.00	100.00
40.0-41.0	0.56	205.27	0.26	96.20	87.0-88.0	0.00	213.38	0.00	100.00
41.0-42.0	0.54	205.81	0.25	96.45	88.0-89.0	0.00	213.38	0.00	100.00
42.0-43.0	0.52	206.33	0.24	96.70	89.0-90.0	0.00	213.38	0.00	100.00
43.0-44.0	0.50	206.83	0.24	96.93	90.0-91.0	0.00	213.38	0.00	100.00
44.0-45.0	0.49	207.32	0.23	97.16	91.0-92.0	0.00	213.38	0.00	100.00
45.0-46.0	0.47	207.79	0.22	97.38	92.0-93.0	0.00	213.38	0.00	100.00
46.0-47.0	0.46	208.25	0.21	97.60	93.0-94.0	0.00	213.38	0.00	100.00

IES Indoor Report


Photometric Filename:DL43-05-PR-01 RA90 4000K 15D.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	213.38	0.00	100.00	141.0-142.0	0.00	213.38	0.00	100.00
95.0-96.0	0.00	213.38	0.00	100.00	142.0-143.0	0.00	213.38	0.00	100.00
96.0-97.0	0.00	213.38	0.00	100.00	143.0-144.0	0.00	213.38	0.00	100.00
97.0-98.0	0.00	213.38	0.00	100.00	144.0-145.0	0.00	213.38	0.00	100.00
98.0-99.0	0.00	213.38	0.00	100.00	145.0-146.0	0.00	213.38	0.00	100.00
99.0-100.0	0.00	213.38	0.00	100.00	146.0-147.0	0.00	213.38	0.00	100.00
100.0-101.0	0.00	213.38	0.00	100.00	147.0-148.0	0.00	213.38	0.00	100.00
101.0-102.0	0.00	213.38	0.00	100.00	148.0-149.0	0.00	213.38	0.00	100.00
102.0-103.0	0.00	213.38	0.00	100.00	149.0-150.0	0.00	213.38	0.00	100.00
103.0-104.0	0.00	213.38	0.00	100.00	150.0-151.0	0.00	213.38	0.00	100.00
104.0-105.0	0.00	213.38	0.00	100.00	151.0-152.0	0.00	213.38	0.00	100.00
105.0-106.0	0.00	213.38	0.00	100.00	152.0-153.0	0.00	213.38	0.00	100.00
106.0-107.0	0.00	213.38	0.00	100.00	153.0-154.0	0.00	213.38	0.00	100.00
107.0-108.0	0.00	213.38	0.00	100.00	154.0-155.0	0.00	213.38	0.00	100.00
108.0-109.0	0.00	213.38	0.00	100.00	155.0-156.0	0.00	213.38	0.00	100.00
109.0-110.0	0.00	213.38	0.00	100.00	156.0-157.0	0.00	213.38	0.00	100.00
110.0-111.0	0.00	213.38	0.00	100.00	157.0-158.0	0.00	213.38	0.00	100.00
111.0-112.0	0.00	213.38	0.00	100.00	158.0-159.0	0.00	213.38	0.00	100.00
112.0-113.0	0.00	213.38	0.00	100.00	159.0-160.0	0.00	213.38	0.00	100.00
113.0-114.0	0.00	213.38	0.00	100.00	160.0-161.0	0.00	213.38	0.00	100.00
114.0-115.0	0.00	213.38	0.00	100.00	161.0-162.0	0.00	213.38	0.00	100.00
115.0-116.0	0.00	213.38	0.00	100.00	162.0-163.0	0.00	213.38	0.00	100.00
116.0-117.0	0.00	213.38	0.00	100.00	163.0-164.0	0.00	213.38	0.00	100.00
117.0-118.0	0.00	213.38	0.00	100.00	164.0-165.0	0.00	213.38	0.00	100.00
118.0-119.0	0.00	213.38	0.00	100.00	165.0-166.0	0.00	213.38	0.00	100.00
119.0-120.0	0.00	213.38	0.00	100.00	166.0-167.0	0.00	213.38	0.00	100.00
120.0-121.0	0.00	213.38	0.00	100.00	167.0-168.0	0.00	213.38	0.00	100.00
121.0-122.0	0.00	213.38	0.00	100.00	168.0-169.0	0.00	213.38	0.00	100.00
122.0-123.0	0.00	213.38	0.00	100.00	169.0-170.0	0.00	213.38	0.00	100.00
123.0-124.0	0.00	213.38	0.00	100.00	170.0-171.0	0.00	213.38	0.00	100.00
124.0-125.0	0.00	213.38	0.00	100.00	171.0-172.0	0.00	213.38	0.00	100.00
125.0-126.0	0.00	213.38	0.00	100.00	172.0-173.0	0.00	213.38	0.00	100.00
126.0-127.0	0.00	213.38	0.00	100.00	173.0-174.0	0.00	213.38	0.00	100.00
127.0-128.0	0.00	213.38	0.00	100.00	174.0-175.0	0.00	213.38	0.00	100.00
128.0-129.0	0.00	213.38	0.00	100.00	175.0-176.0	0.00	213.38	0.00	100.00
129.0-130.0	0.00	213.38	0.00	100.00	176.0-177.0	0.00	213.38	0.00	100.00
130.0-131.0	0.00	213.38	0.00	100.00	177.0-178.0	0.00	213.38	0.00	100.00
131.0-132.0	0.00	213.38	0.00	100.00	178.0-179.0	0.00	213.38	0.00	100.00
132.0-133.0	0.00	213.38	0.00	100.00	179.0-180.0	0.00	213.38	0.00	100.00
133.0-134.0	0.00	213.38	0.00	100.00					
134.0-135.0	0.00	213.38	0.00	100.00					
135.0-136.0	0.00	213.38	0.00	100.00					
136.0-137.0	0.00	213.38	0.00	100.00					
137.0-138.0	0.00	213.38	0.00	100.00					
138.0-139.0	0.00	213.38	0.00	100.00					
139.0-140.0	0.00	213.38	0.00	100.00					
140.0-141.0	0.00	213.38	0.00	100.00					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



Plane ISO-Illuminance Diagram

Lum. Name:DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Deparment
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2020/12/25

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 120.17
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0


IES Indoor Report

Photometric Filename:DL43-05-PR-01 RA90 4000K 15D.IES

3D Plane ISO Illuminance Diagram

Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name:DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Deparment
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2020/12/25


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:1081.53lx,2.0deg
Plane Maximum Lighting Intensity and @Angle:1083.511cd,0deg

Illuminance-Distance Diagram

Lum. Name:DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Deparment
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2020/12/25



Indoor Luminance Limiting Curves

Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	0	0	0	0	0	0	0	0	0
C90	0	0	0	0	0	0	0	0	0

Luminance Limiting Curve



Luminous Size: Length(m)=0.000 Width(m)=0.000 Height(m)=0.000 Area(m^2)=0.000000

Luminous Type: Without Luminous Side


Luminous Curves: C0-C180 Color: C90-C270 Color:

IES Indoor Report

Photometric Filename:DL43-05-PR-01 RA90 4000K 15D.IES

Indoor Budgetary Estimate Table

Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name:DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Deparment
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2020/12/25

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	107	107	105	104	103	102	101	100	99	98	96
2	111	107	104	102	109	106	103	101	103	100	98	100	98	96	97	96	94	93
3	107	103	99	96	106	101	98	95	99	96	94	97	94	92	95	93	91	90
4	104	99	95	92	102	98	94	91	96	92	90	94	91	89	92	90	88	87
5	101	95	91	88	100	94	90	87	92	89	87	91	88	86	90	87	85	84
6	98	92	87	84	97	91	87	84	90	86	84	88	85	83	87	85	83	82
7	95	89	85	82	94	88	84	81	87	84	81	86	83	81	85	82	80	79
8	93	86	82	79	92	86	82	79	85	81	79	84	81	78	83	80	78	77
9	90	84	80	77	89	83	79	77	82	79	76	82	78	76	81	78	76	75
10	88	81	77	75	87	81	77	75	80	77	74	80	76	74	79	76	74	73

Unified Glare Rating Table

Lum. Name: DL43-05-PR-03 RA90 4000K 15D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Deparment
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Room Size	Vewed crosswise					Vewed endwise					
X=2H Y=2H	-6.2	-5.2	-5.8	-4.9	-4.6	-6.2	-5.2	-5.8	-4.9	-4.6	
	Y=3H	-6.4	-5.6	-6.0	-5.2	-4.9	-6.4	-5.6	-6.0	-5.2	-4.9
	Y=4H	-6.5	-5.7	-6.1	-5.4	-5.0	-6.5	-5.7	-6.1	-5.4	-5.0
	Y=6H	-6.6	-5.9	-6.2	-5.5	-5.1	-6.6	-5.9	-6.2	-5.5	-5.1
	Y=8H	-6.7	-6.0	-6.2	-5.6	-5.2	-6.7	-6.0	-6.2	-5.6	-5.2
	Y=12H	-6.7	-6.1	-6.3	-5.7	-5.3	-6.7	-6.1	-6.3	-5.7	-5.3
X=4H Y=2H	-6.5	-5.7	-6.1	-5.4	-5.0	-6.5	-5.7	-6.1	-5.4	-5.0	
	Y=3H	-6.7	-6.1	-6.3	-5.7	-5.3	-6.7	-6.1	-6.3	-5.7	-5.3
	Y=4H	-6.9	-6.3	-6.4	-5.9	-5.4	-6.9	-6.3	-6.4	-5.9	-5.4
	Y=6H	-7.0	-6.5	-6.5	-6.0	-5.6	-7.0	-6.5	-6.5	-6.0	-5.6
	Y=8H	-7.0	-6.6	-6.6	-6.1	-5.7	-7.0	-6.6	-6.6	-6.1	-5.7
	Y=12H	-7.1	-6.7	-6.6	-6.2	-5.8	-7.1	-6.7	-6.6	-6.2	-5.8
X=8H Y=4H	-7.0	-6.6	-6.6	-6.1	-5.7	-7.0	-6.6	-6.6	-6.1	-5.7	
	Y=6H	-7.2	-6.8	-6.7	-6.3	-5.8	-7.2	-6.8	-6.7	-6.3	-5.8
	Y=8H	-7.2	-6.9	-6.7	-6.4	-5.9	-7.2	-6.9	-6.7	-6.4	-5.9
	Y=12H	-7.3	-7.0	-6.8	-6.5	-6.0	-7.3	-7.0	-6.8	-6.5	-6.0
X=12H Y=4H	-7.1	-6.7	-6.6	-6.2	-5.8	-7.1	-6.7	-6.6	-6.2	-5.8	
	Y=6H	-7.2	-6.9	-6.7	-6.5	-5.9	-7.2	-6.9	-6.7	-6.5	-5.9
	Y=8H	-7.3	-7.0	-6.8	-6.5	-6.0	-7.3	-7.0	-6.8	-6.5	-6.0
Variations with the objerver position at spacings											
S=1.0H	0.0/0.0					0.0/0.0					
S=1.5H	0.0/0.0					0.0/0.0					
S=2.0H	0.0/0.0					0.0/0.0					
Reduced UGR Table:											
Nordic Standard Table:	BK0					BK0					
Correction Value	0.0					0.0					

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:DL43-05-PR-01 RA90 4000K 15D.IES

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1032.22	1032.22	1032.22	1032.22
γ 1.0	1065.49	1059.85	991.47	1001.51
γ 2.0	1083.51	1061.75	954.80	960.23
γ 3.0	1077.35	1043.77	919.67	914.93
γ 4.0	1053.51	1018.63	880.63	862.09
γ 5.0	1026.50	990.10	836.79	803.66
γ 6.0	997.96	962.29	784.50	739.01
γ 7.0	963.06	931.15	724.75	670.59
γ 8.0	922.69	891.84	661.64	602.46
γ 9.0	873.19	841.41	596.40	535.40
γ 10.0	815.99	783.25	532.70	472.12
γ 11.0	751.78	720.20	471.54	411.83
γ 12.0	684.14	654.59	409.64	353.77
γ 13.0	613.78	587.32	348.65	298.85
γ 14.0	544.68	521.25	292.77	249.03
γ 15.0	477.70	455.54	237.53	203.78
γ 16.0	412.66	391.83	192.58	165.23
γ 17.0	350.94	330.55	150.03	132.17
γ 18.0	294.37	273.63	116.83	104.54
γ 19.0	242.97	221.53	90.95	81.91
γ 20.0	197.85	177.60	71.33	64.50
γ 21.0	159.20	141.62	56.14	51.74
γ 22.0	126.86	112.13	45.28	42.83
γ 23.0	101.18	89.29	37.28	36.34
γ 24.0	80.78	71.96	31.31	31.41
γ 25.0	65.05	58.71	26.74	27.46
γ 26.0	53.75	48.83	23.21	24.21
γ 27.0	45.32	41.29	20.20	21.44
γ 28.0	39.08	35.53	17.64	19.08
γ 29.0	34.29	31.08	15.45	17.13
γ 30.0	30.36	27.33	13.54	15.43
γ 31.0	27.20	24.13	11.93	13.94
γ 32.0	24.41	21.37	10.51	12.64
γ 33.0	21.92	18.96	9.26	11.46
γ 34.0	19.82	16.82	8.10	10.45
γ 35.0	18.03	14.87	7.22	9.55
γ 36.0	16.40	13.18	6.68	8.63
γ 37.0	14.90	11.65	6.30	7.98
γ 38.0	13.52	10.31	5.97	7.64
γ 39.0	12.15	9.52	5.69	7.32
γ 40.0	11.05	8.80	5.44	7.04
γ 41.0	10.30	8.15	5.25	6.80
γ 42.0	9.62	7.57	5.08	6.59
γ 43.0	9.00	7.04	4.93	6.39
γ 44.0	8.44	6.57	4.78	6.23
γ 45.0	7.96	6.16	4.60	6.04
γ 46.0	7.50	5.77	4.44	5.86

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	7.11	5.39	4.23	5.65
γ 48.0	6.73	5.06	3.99	5.40
γ 49.0	6.37	4.72	3.73	5.14
γ 50.0	6.03	4.37	3.47	4.87
γ 51.0	5.68	4.02	3.21	4.60
γ 52.0	5.32	3.69	2.94	4.32
γ 53.0	4.96	3.36	2.70	4.04
γ 54.0	4.61	3.04	2.45	3.78
γ 55.0	4.28	2.72	2.22	3.53
γ 56.0	3.95	2.45	1.98	3.29
γ 57.0	3.64	2.19	1.75	3.04
γ 58.0	3.38	1.93	1.52	2.82
γ 59.0	3.12	1.69	1.31	2.58
γ 60.0	2.86	1.45	1.10	2.35
γ 61.0	2.61	1.24	0.90	2.13
γ 62.0	2.36	1.01	0.70	1.91
γ 63.0	2.13	0.82	0.49	1.70
γ 64.0	1.90	0.61	0.31	1.49
γ 65.0	1.69	0.41	0.13	1.29
γ 66.0	1.48	0.23	0.00	1.09
γ 67.0	1.27	0.05	0.00	0.90
γ 68.0	1.08	0.00	0.00	0.70
γ 69.0	0.89	0.00	0.00	0.52
γ 70.0	0.70	0.00	0.00	0.35
γ 71.0	0.53	0.00	0.00	0.18
γ 72.0	0.36	0.00	0.00	0.03
γ 73.0	0.19	0.00	0.00	0.00
γ 74.0	0.03	0.00	0.00	0.00
γ 75.0	0.00	0.00	0.00	0.00
γ 76.0	0.00	0.00	0.00	0.00
γ 77.0	0.00	0.00	0.00	0.00
γ 78.0	0.00	0.00	0.00	0.00
γ 79.0	0.00	0.00	0.00	0.00
γ 80.0	0.00	0.00	0.00	0.00
γ 81.0	0.00	0.00	0.00	0.00
γ 82.0	0.00	0.00	0.00	0.00
γ 83.0	0.00	0.00	0.00	0.00
γ 84.0	0.00	0.00	0.00	0.00
γ 85.0	0.00	0.00	0.00	0.00
γ 86.0	0.00	0.00	0.00	0.00
γ 87.0	0.00	0.00	0.00	0.00
γ 88.0	0.00	0.00	0.00	0.00
γ 89.0	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00
γ 91.0	0.00	0.00	0.00	0.00
γ 92.0	0.00	0.00	0.00	0.00
γ 93.0	0.00	0.00	0.00	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 96.0	0.00	0.00	0.00	0.00
γ 97.0	0.00	0.00	0.00	0.00
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 131.0	0.00	0.00	0.00	0.00
γ 132.0	0.00	0.00	0.00	0.00
γ 133.0	0.00	0.00	0.00	0.00
γ 134.0	0.00	0.00	0.00	0.00
γ 135.0	0.00	0.00	0.00	0.00
γ 136.0	0.00	0.00	0.00	0.00
γ 137.0	0.00	0.00	0.00	0.00
γ 138.0	0.00	0.00	0.00	0.00
γ 139.0	0.00	0.00	0.00	0.00
γ 140.0	0.00	0.00	0.00	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00
γ 144.0	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.00	0.00	0.00
γ 146.0	0.00	0.00	0.00	0.00
γ 147.0	0.00	0.00	0.00	0.00
γ 148.0	0.00	0.00	0.00	0.00
γ 149.0	0.00	0.00	0.00	0.00
γ 150.0	0.00	0.00	0.00	0.00
γ 151.0	0.00	0.00	0.00	0.00
γ 152.0	0.00	0.00	0.00	0.00
γ 153.0	0.00	0.00	0.00	0.00
γ 154.0	0.00	0.00	0.00	0.00
γ 155.0	0.00	0.00	0.00	0.00
γ 156.0	0.00	0.00	0.00	0.00
γ 157.0	0.00	0.00	0.00	0.00
γ 158.0	0.00	0.00	0.00	0.00
γ 159.0	0.00	0.00	0.00	0.00
γ 160.0	0.00	0.00	0.00	0.00
γ 161.0	0.00	0.00	0.00	0.00
γ 162.0	0.00	0.00	0.00	0.00
γ 163.0	0.00	0.00	0.00	0.00
γ 164.0	0.00	0.00	0.00	0.00
γ 165.0	0.00	0.00	0.00	0.00
γ 166.0	0.00	0.00	0.00	0.00
γ 167.0	0.00	0.00	0.00	0.00
γ 168.0	0.00	0.00	0.00	0.00
γ 169.0	0.00	0.00	0.00	0.00
γ 170.0	0.00	0.00	0.00	0.00
γ 171.0	0.00	0.00	0.00	0.00
γ 172.0	0.00	0.00	0.00	0.00
γ 173.0	0.00	0.00	0.00	0.00
γ 174.0	0.00	0.00	0.00	0.00
γ 175.0	0.00	0.00	0.00	0.00
γ 176.0	0.00	0.00	0.00	0.00
γ 177.0	0.00	0.00	0.00	0.00
γ 178.0	0.00	0.00	0.00	0.00
γ 179.0	0.00	0.00	0.00	0.00
γ 180.0	0.00	0.00	0.00	0.00