




FEATURES

- Made of die-casting.
- Powder coating finish from AkzoNobel.
- Interchangeable faceplate with magnetic design.
- High density COB with uniform lighting distribution.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/110mA
Power	5W
Rated Input Current	0.025A
THD	<30%
PF value	>0.84
Ingress Protection	IP54
Operating Temperature	-10–40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>80, Ra>90
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	84lm/W

Packaging

Box Dimensions	L65 x W65 x H110mm
Box Net Weight	0.136Kg
Box Gross Weight	0.161Kg
Carton Dimensions	L340 x W340 x H240 mm/50 PCS
Carton Net Weight	6.800Kg
Carton Gross Weight	8.050Kg



Specifications (White)

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	346lm	72lm/W	CRI 90+	15°	303lm	63lm/W
		24°	349lm	76lm/W		24°	319lm	65lm/W
		36°	366lm	76lm/W		36°	313lm	65lm/W
		50°	287lm	62lm/W		50°	255lm	52lm/W
3000K		15°	374lm	80lm/W		15°	293lm	61lm/W
		24°	396lm	83lm/W		24°	309lm	65lm/W
		36°	410lm	84lm/W		36°	296lm	63lm/W
		50°	332lm	67lm/W		50°	242lm	52lm/W
4000K		15°	374lm	76lm/W		15°	318lm	66lm/W
		24°	395lm	80lm/W		24°	335lm	70lm/W
		36°	394lm	80lm/W		36°	329lm	69lm/W
		50°	314lm	65lm/W		50°	262lm	57lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

Specifications (Black)

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	304lm	65lm/W	CRI 90+	15°	272lm	56lm/W
		24°	332lm	69lm/W		24°	287lm	59lm/W
		36°	340lm	70lm/W		36°	286lm	59lm/W
		50°	258lm	53lm/W		50°	218lm	45lm/W
3000K		15°	347lm	71lm/W		15°	280lm	57lm/W
		24°	366lm	75m/W		24°	287lm	62lm/W
		36°	366lm	76lm/W		36°	293lm	60lm/W
		50°	276lm	57lm/W		50°	225lm	46lm/W
4000K		15°	355lm	73lm/W		15°	297lm	62lm/W
		24°	389lm	80lm/W		24°	304lm	66lm/W
		36°	387lm	80lm/W		36°	313lm	65lm/W
		50°	279lm	59lm/W		50°	235lm	49lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS