



Indoor Luminaire Photometric Data

Description Information

Luminary Name: DL43-05-XX-02 4000K RA90 50D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2020/06/24
Manufacture: Shenzhen Norming Lighting Co., Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.050m*0.050m*0.072m		Lum. Area (m2):0.006	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 308.260	Luminary Flux(lm): 308.262	Field Angle(10%Imax): 78.6(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 295.614lm 95.90%	
Rated Voltage(V):	Luminary EER(lm/W): 64.788	Up Lumens&Percent: 12.648lm 4.10%	
Tested Power(W): 4.758	Max. Candela(cd): 438.508	S/MH: C0_a180=0.794 C90_270=0.786	
Lamps' Inside: 1	Max Cand@Ang. (°): C=270.0 γ=9.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.0, 0.022, 0.864	Beam Angle(50%Imax): 43.8(°)	ErP ϕ use(90°): 264.372lm	
Lamp Size (W*L*H):0.050m*0.050m*0.072m	Left=-18.9°, Right=24.9°	IRF(%): 292.266	



2D Plane Light Intensity Distribution Curve


Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24



3D Light Intensity Distribution Modal

Lum. Name:DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2020/06/24

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:DL43-05-XX-02 4000K RA90 50D.IES

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.35	0.35	0.11	0.11	47.0-48.0	1.22	278.26	0.40	90.27
1.0-2.0	1.07	1.42	0.35	0.46	48.0-49.0	1.08	279.34	0.35	90.62
2.0-3.0	1.78	3.20	0.58	1.04	49.0-50.0	0.96	280.30	0.31	90.93
3.0-4.0	2.49	5.69	0.81	1.84	50.0-51.0	0.86	281.16	0.28	91.21
4.0-5.0	3.19	8.88	1.04	2.88	51.0-52.0	0.77	281.93	0.25	91.46
5.0-6.0	3.89	12.77	1.26	4.14	52.0-53.0	0.69	282.62	0.22	91.68
6.0-7.0	4.58	17.35	1.49	5.63	53.0-54.0	0.63	283.26	0.21	91.89
7.0-8.0	5.26	22.61	1.71	7.34	54.0-55.0	0.58	283.84	0.19	92.08
8.0-9.0	5.91	28.52	1.92	9.25	55.0-56.0	0.54	284.38	0.18	92.25
9.0-10.0	6.53	35.05	2.12	11.37	56.0-57.0	0.51	284.90	0.17	92.42
10.0-11.0	7.12	42.17	2.31	13.68	57.0-58.0	0.49	285.39	0.16	92.58
11.0-12.0	7.66	49.83	2.48	16.16	58.0-59.0	0.47	285.86	0.15	92.73
12.0-13.0	8.14	57.97	2.64	18.80	59.0-60.0	0.46	286.32	0.15	92.88
13.0-14.0	8.56	66.53	2.78	21.58	60.0-61.0	0.44	286.76	0.14	93.03
14.0-15.0	8.91	75.44	2.89	24.47	61.0-62.0	0.43	287.19	0.14	93.17
15.0-16.0	9.19	84.63	2.98	27.45	62.0-63.0	0.42	287.61	0.14	93.30
16.0-17.0	9.41	94.04	3.05	30.51	63.0-64.0	0.41	288.02	0.13	93.43
17.0-18.0	9.56	103.60	3.10	33.61	64.0-65.0	0.40	288.42	0.13	93.56
18.0-19.0	9.65	113.25	3.13	36.74	65.0-66.0	0.39	288.81	0.13	93.69
19.0-20.0	9.68	122.92	3.14	39.88	66.0-67.0	0.38	289.18	0.12	93.81
20.0-21.0	9.65	132.57	3.13	43.01	67.0-68.0	0.37	289.55	0.12	93.93
21.0-22.0	9.57	142.14	3.11	46.11	68.0-69.0	0.36	289.90	0.12	94.05
22.0-23.0	9.45	151.60	3.07	49.18	69.0-70.0	0.35	290.25	0.11	94.16
23.0-24.0	9.29	160.88	3.01	52.19	70.0-71.0	0.34	290.59	0.11	94.27
24.0-25.0	9.09	169.97	2.95	55.14	71.0-72.0	0.33	290.92	0.11	94.37
25.0-26.0	8.85	178.82	2.87	58.01	72.0-73.0	0.32	291.23	0.10	94.48
26.0-27.0	8.57	187.39	2.78	60.79	73.0-74.0	0.31	291.54	0.10	94.58
27.0-28.0	8.26	195.65	2.68	63.47	74.0-75.0	0.30	291.85	0.10	94.68
28.0-29.0	7.92	203.57	2.57	66.04	75.0-76.0	0.29	292.14	0.10	94.77
29.0-30.0	7.55	211.12	2.45	68.49	76.0-77.0	0.29	292.43	0.09	94.86
30.0-31.0	7.15	218.26	2.32	70.81	77.0-78.0	0.28	292.71	0.09	94.95
31.0-32.0	6.73	224.99	2.18	72.99	78.0-79.0	0.27	292.98	0.09	95.04
32.0-33.0	6.29	231.29	2.04	75.03	79.0-80.0	0.26	293.24	0.09	95.13
33.0-34.0	5.84	237.13	1.89	76.92	80.0-81.0	0.26	293.50	0.08	95.21
34.0-35.0	5.38	242.51	1.75	78.67	81.0-82.0	0.25	293.76	0.08	95.29
35.0-36.0	4.93	247.43	1.60	80.27	82.0-83.0	0.25	294.00	0.08	95.37
36.0-37.0	4.47	251.91	1.45	81.72	83.0-84.0	0.24	294.25	0.08	95.45
37.0-38.0	4.03	255.94	1.31	83.03	84.0-85.0	0.24	294.48	0.08	95.53
38.0-39.0	3.61	259.55	1.17	84.20	85.0-86.0	0.23	294.72	0.08	95.61
39.0-40.0	3.22	262.77	1.04	85.24	86.0-87.0	0.23	294.95	0.07	95.68
40.0-41.0	2.85	265.63	0.93	86.17	87.0-88.0	0.23	295.17	0.07	95.75
41.0-42.0	2.53	268.15	0.82	86.99	88.0-89.0	0.22	295.40	0.07	95.83
42.0-43.0	2.23	270.39	0.72	87.71	89.0-90.0	0.22	295.61	0.07	95.90
43.0-44.0	1.97	272.36	0.64	88.35	90.0-91.0	0.21	295.83	0.07	95.97
44.0-45.0	1.75	274.11	0.57	88.92	91.0-92.0	0.21	296.04	0.07	96.04
45.0-46.0	1.55	275.66	0.50	89.42	92.0-93.0	0.21	296.25	0.07	96.10
46.0-47.0	1.38	277.04	0.45	89.87	93.0-94.0	0.21	296.45	0.07	96.17

IES Indoor Report


Photometric Filename:DL43-05-XX-02 4000K RA90 50D.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.20	296.66	0.07	96.24	141.0-142.0	0.16	304.58	0.05	98.81
95.0-96.0	0.20	296.86	0.06	96.30	142.0-143.0	0.16	304.74	0.05	98.86
96.0-97.0	0.20	297.05	0.06	96.36	143.0-144.0	0.16	304.90	0.05	98.91
97.0-98.0	0.19	297.25	0.06	96.43	144.0-145.0	0.16	305.05	0.05	98.96
98.0-99.0	0.19	297.44	0.06	96.49	145.0-146.0	0.15	305.21	0.05	99.01
99.0-100.0	0.19	297.63	0.06	96.55	146.0-147.0	0.15	305.36	0.05	99.06
100.0-101.0	0.19	297.82	0.06	96.61	147.0-148.0	0.15	305.51	0.05	99.11
101.0-102.0	0.18	298.00	0.06	96.67	148.0-149.0	0.15	305.66	0.05	99.16
102.0-103.0	0.18	298.18	0.06	96.73	149.0-150.0	0.15	305.80	0.05	99.20
103.0-104.0	0.18	298.36	0.06	96.79	150.0-151.0	0.14	305.95	0.05	99.25
104.0-105.0	0.18	298.54	0.06	96.85	151.0-152.0	0.14	306.09	0.05	99.30
105.0-106.0	0.18	298.72	0.06	96.90	152.0-153.0	0.14	306.23	0.04	99.34
106.0-107.0	0.17	298.89	0.06	96.96	153.0-154.0	0.14	306.36	0.04	99.38
107.0-108.0	0.17	299.06	0.06	97.02	154.0-155.0	0.13	306.50	0.04	99.43
108.0-109.0	0.17	299.23	0.06	97.07	155.0-156.0	0.13	306.62	0.04	99.47
109.0-110.0	0.17	299.40	0.06	97.13	156.0-157.0	0.12	306.75	0.04	99.51
110.0-111.0	0.17	299.57	0.05	97.18	157.0-158.0	0.12	306.87	0.04	99.55
111.0-112.0	0.17	299.74	0.05	97.24	158.0-159.0	0.12	306.99	0.04	99.59
112.0-113.0	0.17	299.90	0.05	97.29	159.0-160.0	0.11	307.10	0.04	99.62
113.0-114.0	0.16	300.07	0.05	97.34	160.0-161.0	0.11	307.21	0.04	99.66
114.0-115.0	0.16	300.23	0.05	97.40	161.0-162.0	0.10	307.31	0.03	99.69
115.0-116.0	0.16	300.40	0.05	97.45	162.0-163.0	0.10	307.41	0.03	99.72
116.0-117.0	0.16	300.56	0.05	97.50	163.0-164.0	0.09	307.50	0.03	99.75
117.0-118.0	0.16	300.72	0.05	97.55	164.0-165.0	0.09	307.59	0.03	99.78
118.0-119.0	0.16	300.88	0.05	97.61	165.0-166.0	0.08	307.68	0.03	99.81
119.0-120.0	0.16	301.04	0.05	97.66	166.0-167.0	0.08	307.75	0.03	99.84
120.0-121.0	0.16	301.20	0.05	97.71	167.0-168.0	0.07	307.83	0.02	99.86
121.0-122.0	0.16	301.36	0.05	97.76	168.0-169.0	0.07	307.90	0.02	99.88
122.0-123.0	0.16	301.52	0.05	97.81	169.0-170.0	0.06	307.96	0.02	99.90
123.0-124.0	0.16	301.68	0.05	97.87	170.0-171.0	0.06	308.02	0.02	99.92
124.0-125.0	0.16	301.84	0.05	97.92	171.0-172.0	0.05	308.07	0.02	99.94
125.0-126.0	0.16	302.00	0.05	97.97	172.0-173.0	0.05	308.11	0.01	99.95
126.0-127.0	0.16	302.17	0.05	98.02	173.0-174.0	0.04	308.15	0.01	99.96
127.0-128.0	0.16	302.33	0.05	98.07	174.0-175.0	0.03	308.19	0.01	99.98
128.0-129.0	0.16	302.49	0.05	98.13	175.0-176.0	0.03	308.21	0.01	99.98
129.0-130.0	0.16	302.65	0.05	98.18	176.0-177.0	0.02	308.23	0.01	99.99
130.0-131.0	0.16	302.81	0.05	98.23	177.0-178.0	0.02	308.25	0.01	100.00
131.0-132.0	0.16	302.97	0.05	98.28	178.0-179.0	0.01	308.26	0.00	100.00
132.0-133.0	0.16	303.13	0.05	98.34	179.0-180.0	0.00	308.26	0.00	100.00
133.0-134.0	0.16	303.30	0.05	98.39					
134.0-135.0	0.16	303.46	0.05	98.44					
135.0-136.0	0.16	303.62	0.05	98.49					
136.0-137.0	0.16	303.78	0.05	98.55					
137.0-138.0	0.16	303.94	0.05	98.60					
138.0-139.0	0.16	304.10	0.05	98.65					
139.0-140.0	0.16	304.26	0.05	98.70					
140.0-141.0	0.16	304.42	0.05	98.76					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24




Maximum Light Intensity(cd): 438.51

Maximum Cand.@Angle: H=-0.0°,V=-9.0°

Plane ISO-Illuminance Diagram

Lum. Name:DL43-05-XX-02 4000K RA90 50D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 47.08
Working Plane Maximum Illuminance Position(d/h):H-0.1 V-0.0

3D Plane ISO Illuminance Diagram

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:369.24lx,0.0deg
Plane Maximum Lighting Intensity and @Angle:369.242cd,0deg

Illuminance-Distance Diagram

Lum. Name:DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2020/06/24



Indoor Luminance Limiting Curves

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	6720	3717	2291	1872	1791	1818	2012	2558	4482
C90	6554	3449	1925	1552	1488	1511	1667	2125	3766

Luminance Limiting Curve




Luminous Size: Length(m)=0.050 Width(m)=0.050 Height(m)=0.072 Area(m^2)=0.006100

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24



Indoor Coefficient of Utilization Table

Lum. Name:DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2020/06/24

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	118	118	118	118	115	115	115	115	109	109	109	103	103	103	98	98	98	96
1	112	109	106	104	109	106	104	102	102	100	98	97	96	94	93	92	91	89
2	106	101	97	93	103	99	95	92	95	92	89	91	89	86	88	86	84	82
3	101	94	89	84	98	92	87	83	89	85	82	86	83	80	83	80	78	76
4	95	88	82	77	93	86	81	77	83	79	75	81	77	74	79	75	73	71
5	90	82	76	72	89	81	75	71	78	74	70	76	72	69	74	71	68	66
6	86	77	71	66	84	76	70	66	74	69	65	72	68	64	70	67	64	62
7	82	72	66	62	80	71	66	62	70	65	61	68	64	60	67	63	60	58
8	78	68	62	58	76	68	62	58	66	61	57	65	60	57	63	59	56	55
9	74	65	59	55	73	64	58	54	63	58	54	61	57	54	60	56	53	52
10	71	61	55	52	70	61	55	51	60	54	51	58	54	51	57	53	50	49

Unified Glare Rating Table

Lum. Name: DL43-05-XX-02 4000K RA90 50D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/06/24

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	15.0	16.0	15.4	16.4	16.8	14.4	15.4	14.8	15.8	16.2
	15.1	16.0	15.5	16.4	16.9	14.4	15.4	14.9	15.8	16.3
	15.2	16.1	15.7	16.5	17.0	14.5	15.4	15.0	15.8	16.3
	15.4	16.2	15.9	16.6	17.1	14.7	15.5	15.2	15.9	16.4
	15.5	16.3	16.1	16.8	17.3	14.8	15.6	15.3	16.0	16.6
	15.8	16.5	16.3	17.0	17.5	15.0	15.7	15.5	16.2	16.7
X=4H Y=2H	14.8	15.7	15.3	16.1	16.6	14.2	15.1	14.7	15.5	16.0
	15.0	15.7	15.5	16.2	16.7	14.4	15.1	14.9	15.6	16.1
	15.2	15.9	15.7	16.4	16.9	14.5	15.2	15.0	15.7	16.2
	15.6	16.2	16.1	16.7	17.3	14.9	15.4	15.4	16.0	16.5
	15.9	16.4	16.4	16.9	17.5	15.1	15.6	15.6	16.2	16.7
	16.3	16.8	16.8	17.3	17.9	15.5	15.9	16.0	16.5	17.1
X=8H Y=4H	15.2	15.8	15.8	16.3	16.9	14.6	15.1	15.1	15.6	16.2
	15.8	16.2	16.4	16.8	17.4	15.0	15.5	15.6	16.1	16.7
	16.2	16.6	16.8	17.2	17.8	15.4	15.8	16.0	16.4	17.0
	16.8	17.2	17.4	17.8	18.4	16.0	16.4	16.6	16.9	17.6
X=12H Y=4H	15.2	15.7	15.8	16.3	16.8	14.5	15.0	15.1	15.6	16.2
	15.8	16.2	16.4	16.8	17.4	15.1	15.5	15.7	16.0	16.7
	16.3	16.7	16.9	17.3	17.9	15.6	15.9	16.1	16.5	17.2
Variations with the objerver position at spacings										
S=1.0H	0.1/-0.1					0.1/-0.1				
S=1.5H	0.2/-0.2					0.2/-0.2				
S=2.0H	0.1/-0.2					0.2/-0.2				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	1.6					1.5				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:DL43-05-XX-02 4000K RA90 50D.IES

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	369.24	369.24	369.24	369.24
γ 1.0	364.56	369.81	364.46	387.69
γ 2.0	364.29	360.80	364.12	396.90
γ 3.0	364.22	353.01	363.61	405.53
γ 4.0	364.64	344.98	362.08	413.41
γ 5.0	364.46	338.15	359.88	421.11
γ 6.0	364.49	331.23	356.61	427.40
γ 7.0	363.82	324.71	352.73	432.63
γ 8.0	362.75	318.53	346.79	436.32
γ 9.0	361.33	312.18	340.02	438.51
γ 10.0	359.13	305.60	331.86	438.51
γ 11.0	356.51	298.04	323.17	437.00
γ 12.0	351.68	289.59	312.93	432.92
γ 13.0	345.94	280.60	302.37	427.29
γ 14.0	338.58	270.21	291.03	418.55
γ 15.0	329.63	259.93	279.38	408.73
γ 16.0	319.81	249.18	267.64	395.41
γ 17.0	309.56	238.58	256.04	380.75
γ 18.0	298.09	228.28	244.39	363.73
γ 19.0	287.12	218.10	232.71	345.70
γ 20.0	275.36	208.91	221.57	325.12
γ 21.0	263.74	200.23	210.60	304.31
γ 22.0	252.82	192.11	199.38	282.28
γ 23.0	241.76	184.43	188.46	260.40
γ 24.0	230.95	177.10	177.75	238.35
γ 25.0	220.74	170.51	166.55	216.58
γ 26.0	210.36	164.18	155.51	194.94
γ 27.0	200.12	157.73	144.38	174.34
γ 28.0	189.78	151.30	133.02	154.47
γ 29.0	179.57	144.89	121.74	135.99
γ 30.0	168.75	137.87	110.47	118.80
γ 31.0	157.93	130.81	99.40	103.42
γ 32.0	146.61	123.25	88.69	89.51
γ 33.0	135.07	115.30	78.63	77.21
γ 34.0	123.36	107.01	69.05	66.24
γ 35.0	111.96	98.46	60.45	56.61
γ 36.0	100.71	89.78	52.49	48.30
γ 37.0	89.72	81.07	45.28	41.21
γ 38.0	79.39	72.61	38.95	35.11
γ 39.0	69.71	64.63	33.37	29.81
γ 40.0	60.75	56.97	28.51	25.43
γ 41.0	52.65	49.97	24.43	21.87
γ 42.0	45.40	43.53	21.15	19.12
γ 43.0	39.03	37.64	18.37	16.96
γ 44.0	33.55	32.53	15.99	15.09
γ 45.0	28.99	28.27	13.91	13.52
γ 46.0	25.18	24.51	12.09	12.11

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	21.97	21.24	10.51	10.85
γ 48.0	19.17	18.35	9.14	9.74
γ 49.0	16.70	15.76	7.97	8.79
γ 50.0	14.58	13.52	7.00	8.00
γ 51.0	12.76	11.60	6.25	7.33
γ 52.0	11.22	10.00	5.66	6.77
γ 53.0	9.93	8.67	5.20	6.32
γ 54.0	8.87	7.59	4.85	5.95
γ 55.0	8.02	6.74	4.58	5.65
γ 56.0	7.32	6.08	4.38	5.42
γ 57.0	6.77	5.60	4.20	5.23
γ 58.0	6.33	5.24	4.06	5.04
γ 59.0	5.99	4.97	3.92	4.89
γ 60.0	5.71	4.74	3.79	4.73
γ 61.0	5.47	4.53	3.68	4.58
γ 62.0	5.24	4.34	3.57	4.44
γ 63.0	5.02	4.16	3.47	4.31
γ 64.0	4.81	3.99	3.36	4.18
γ 65.0	4.62	3.84	3.27	4.06
γ 66.0	4.43	3.67	3.17	3.94
γ 67.0	4.27	3.53	3.08	3.82
γ 68.0	4.09	3.40	2.99	3.71
γ 69.0	3.95	3.28	2.91	3.58
γ 70.0	3.79	3.15	2.82	3.47
γ 71.0	3.66	3.04	2.74	3.38
γ 72.0	3.53	2.93	2.67	3.28
γ 73.0	3.41	2.82	2.58	3.18
γ 74.0	3.29	2.73	2.51	3.10
γ 75.0	3.18	2.63	2.44	2.99
γ 76.0	3.08	2.55	2.38	2.91
γ 77.0	2.97	2.47	2.32	2.83
γ 78.0	2.89	2.39	2.25	2.75
γ 79.0	2.79	2.32	2.19	2.66
γ 80.0	2.71	2.25	2.14	2.59
γ 81.0	2.63	2.19	2.10	2.53
γ 82.0	2.55	2.13	2.05	2.48
γ 83.0	2.50	2.08	2.01	2.42
γ 84.0	2.44	2.05	1.98	2.37
γ 85.0	2.38	2.00	1.94	2.32
γ 86.0	2.34	1.96	1.91	2.27
γ 87.0	2.29	1.92	1.87	2.22
γ 88.0	2.25	1.90	1.85	2.18
γ 89.0	2.20	1.86	1.81	2.15
γ 90.0	2.17	1.83	1.79	2.11
γ 91.0	2.12	1.81	1.77	2.07
γ 92.0	2.09	1.78	1.75	2.05
γ 93.0	2.06	1.76	1.73	2.01

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	2.02	1.74	1.72	1.98
γ 95.0	2.00	1.72	1.68	1.96
γ 96.0	1.97	1.69	1.68	1.94
γ 97.0	1.94	1.67	1.66	1.90
γ 98.0	1.91	1.65	1.64	1.88
γ 99.0	1.89	1.64	1.63	1.86
γ 100.0	1.87	1.62	1.63	1.84
γ 101.0	1.85	1.60	1.61	1.83
γ 102.0	1.83	1.59	1.60	1.81
γ 103.0	1.81	1.58	1.60	1.80
γ 104.0	1.79	1.56	1.60	1.78
γ 105.0	1.77	1.55	1.60	1.77
γ 106.0	1.75	1.54	1.58	1.76
γ 107.0	1.74	1.53	1.59	1.76
γ 108.0	1.73	1.52	1.59	1.75
γ 109.0	1.72	1.51	1.60	1.75
γ 110.0	1.71	1.51	1.59	1.74
γ 111.0	1.69	1.50	1.60	1.74
γ 112.0	1.69	1.50	1.62	1.74
γ 113.0	1.68	1.49	1.62	1.75
γ 114.0	1.68	1.50	1.64	1.75
γ 115.0	1.67	1.50	1.65	1.75
γ 116.0	1.67	1.51	1.64	1.76
γ 117.0	1.68	1.52	1.67	1.77
γ 118.0	1.68	1.53	1.69	1.77
γ 119.0	1.69	1.54	1.70	1.79
γ 120.0	1.69	1.55	1.72	1.80
γ 121.0	1.70	1.57	1.74	1.81
γ 122.0	1.71	1.59	1.77	1.82
γ 123.0	1.73	1.62	1.79	1.85
γ 124.0	1.73	1.64	1.82	1.86
γ 125.0	1.75	1.66	1.85	1.88
γ 126.0	1.77	1.69	1.87	1.91
γ 127.0	1.78	1.72	1.91	1.93
γ 128.0	1.80	1.75	1.94	1.94
γ 129.0	1.83	1.79	1.98	1.97
γ 130.0	1.85	1.83	2.01	1.99
γ 131.0	1.88	1.87	2.03	2.02
γ 132.0	1.91	1.91	2.08	2.05
γ 133.0	1.94	1.95	2.12	2.08
γ 134.0	1.97	1.99	2.16	2.10
γ 135.0	2.00	2.03	2.18	2.14
γ 136.0	2.03	2.07	2.23	2.16
γ 137.0	2.06	2.11	2.27	2.19
γ 138.0	2.11	2.16	2.31	2.23
γ 139.0	2.13	2.18	2.35	2.26
γ 140.0	2.17	2.23	2.39	2.30

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	2.21	2.28	2.43	2.33
γ 142.0	2.25	2.32	2.47	2.37
γ 143.0	2.29	2.35	2.51	2.39
γ 144.0	2.32	2.38	2.54	2.44
γ 145.0	2.36	2.43	2.58	2.47
γ 146.0	2.40	2.47	2.62	2.50
γ 147.0	2.45	2.51	2.66	2.55
γ 148.0	2.47	2.53	2.69	2.58
γ 149.0	2.52	2.58	2.72	2.61
γ 150.0	2.56	2.61	2.77	2.66
γ 151.0	2.59	2.64	2.80	2.70
γ 152.0	2.63	2.67	2.83	2.72
γ 153.0	2.66	2.69	2.86	2.76
γ 154.0	2.70	2.72	2.88	2.80
γ 155.0	2.73	2.76	2.91	2.84
γ 156.0	2.76	2.78	2.94	2.87
γ 157.0	2.80	2.80	2.95	2.90
γ 158.0	2.82	2.83	2.99	2.93
γ 159.0	2.85	2.85	3.01	2.97
γ 160.0	2.88	2.86	3.03	3.00
γ 161.0	2.90	2.88	3.04	3.02
γ 162.0	2.93	2.90	3.06	3.06
γ 163.0	2.96	2.92	3.09	3.08
γ 164.0	2.98	2.93	3.10	3.10
γ 165.0	3.01	2.95	3.12	3.12
γ 166.0	3.03	2.97	3.13	3.14
γ 167.0	3.05	2.99	3.14	3.17
γ 168.0	3.07	3.00	3.16	3.18
γ 169.0	3.09	3.02	3.18	3.19
γ 170.0	3.11	3.04	3.18	3.20
γ 171.0	3.13	3.07	3.20	3.21
γ 172.0	3.15	3.09	3.21	3.23
γ 173.0	3.15	3.11	3.22	3.24
γ 174.0	3.17	3.13	3.23	3.24
γ 175.0	3.20	3.14	3.23	3.25
γ 176.0	3.21	3.16	3.25	3.25
γ 177.0	3.22	3.18	3.26	3.25
γ 178.0	3.23	3.20	3.26	3.25
γ 179.0	3.25	3.21	3.25	3.25
γ 180.0	3.25	3.25	3.25	3.25