



## FEATURES

- Made of die-casting.
- Powder coating finish from AkzoNobel.
- Interchangeable faceplate with magnetic design..
- High density COB with uniform lighting distribution.
- Compatible with leading and trailing edge phase cut dimmers.
- For asymmetric indirect lighting..
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/110mA
Power	5W
Rated Input Current	0.025A
THD	<30%
PF value	>0.84
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>80, Ra>90
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	62lm/W

## Packaging

Box Dimensions	L65 x W65 x H110mm
Box Net Weight	0.122Kg
Box Gross Weight	0.141Kg
Carton Dimensions	L340 x W340 x H240 mm/50 PCS
Carton Net Weight	6.125Kg
Carton Gross Weight	7.650Kg



## Specifications (White)

CCT	Asymmetric Beam Angle		Lumen	Efficacy		Lumen	Efficacy
2700K	20°	CRI 80+	254lm	54lm/W	CRI 90+	237lm	48lm/W
3000K	20°		293lm	59lm/W		230lm	46lm/W
4000K	20°		300lm	62lm/W		248lm	51lm/W

## Specifications (Black)

CCT	Asymmetric Beam Angle		Lumen	Efficacy		Lumen	Efficacy
2700K	20°	CRI 80+	140lm	30lm/W	CRI 90+	131lm	26lm/W
3000K	20°		158lm	32lm/W		126lm	25lm/W
4000K	20°		160lm	32lm/W		127lm	27lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS