



Cut-out: Ø90mm-100mm

## FEATURES

- Compatible with leading and trailing edge phase cut dimmers.
- 3-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/230mA
Power	10W
Rated Input Current	0.05A
PF value	>0.9
Ingress Protection	IP54
Operating Temperature	-10–40 °C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80
Colour temperature	3000K/4000K/5000K
System luminous efficacy up to	98lm/W

## Packaging

Box Dimensions	L115 x W115 x H95mm
Box Net Weight	0.32Kg
Box Gross Weight	0.37Kg
Carton Dimensions	L480 x W365 x H310 mm/36 PCS
Carton Net Weight	11.52Kg
Carton Gross Weight	14.12Kg



Model	CCT		Beam Angle	Lumen	Efficacy
DL44-10-XX-05	3000K	CRI 80+	40°	922lm	90lm/W
DL44-10-XX-05	4000K		40°	974lm	96lm/W
DL44-10-XX-05	5000K		40°	961lm	98lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS