




FEATURES

- Compatible with leading and trailing edge phase cut dimmers.
- 3-year guarantee.



Cut-out: Ø90mm-100mm

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/230mA
Power	10W
Rated Input Current	0.05A
PF value	>0.9
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80
Colour temperature	3000K/4000K/5000K
System luminous efficacy up to	98lm/W

Packaging

Box Dimensions	L115 x W115 x H95mm
Box Net Weight	0.291Kg
Box Gross Weight	0.341Kg
Carton Dimensions	L480 x W365 x H310 mm/36 PCS
Carton Net Weight	10.48Kg
Carton Gross Weight	13.08Kg



Model	CCT		Beam Angle	Lumen	Efficacy
DL44-10-XX-11	3000K	CRI 80+	100°	922lm	90lm/W
DL44-10-XX-11	4000K		100°	974lm	96lm/W
DL44-10-XX-11	5000K		100°	961lm	98lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS