



FEATURES



- Modular Design.
- System power up to 20W.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/350mA
Power	14.2W
Rated Input Current	0.071A
PF value	>0.9
THD	<6%
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Non-dimmable with PHILIPS driver

Optical Data

LED Brand	Bridgelux SMD LED
CRI	Ra > 90
Beam Angle	70°
Colour temperature	2700k/3000K/4000K/5000K 2500k/2700K/3500K/4500K
System luminous efficacy up to	80.2lm/W



Cut-out: Ø100mm

Packaging

Box Dimensions	L165 x W145 x H133mm
Box Net Weight	0.70Kg
Box Gross Weight	0.82Kg
Carton Dimensions	L450 x W345 x H555 mm/24 PCS
Carton Net Weight	16.8Kg
Carton Gross Weight	20.48Kg

Model	CCT		Beam Angle	Lumen	Efficacy	Lumen	Efficacy
DL50-15-XX-01	2700K	CRI 90+	70°	1086lm	73.3lm/W	863.3lm	58.8lm/W
DL50-15-XX-01	3000K		70°	1157lm	80.2lm/W	955lm	65.7lm/W
DL50-15-XX-01	4000K		70°	1133lm	77.4lm/W	932.48lm	63.2lm/W
DL50-15-XX-01	5000K		70°	1170lm	79.8lm/W	940lm	64.69lm/W

Reflector



Model	CCT		Beam Angle	Lumen	Efficacy
DL50-15-XX-01	2500K	CRI 90+	70°	940lm	64.3lm/W
DL50-15-XX-01	2700K		70°	1027lm	71.1lm/W
DL50-15-XX-01	3500K		70°	992.6lm	67.8lm/W
DL50-15-XX-01	4500K		70°	1013lm	69.5lm/W

Reflector



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS