



Cut-out: Ø150mm

## Packaging

Box Dimensions	L210 x W210 x H145mm
Box Net Weight	1.2Kg
Box Gross Weight	1.41Kg
Carton Dimensions	L435 x W435 x H460 mm/12 PCS
Carton Net Weight	14.4Kg
Carton Gross Weight	17.72Kg

## FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/600mA
Power	23.5W
Rated Input Current	0.1175A
PF value	>0.9
THD	<6%
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Non-dimmable with PHILIPS driver

## Optical Data

LED Brand	Bridgelux SMD LED
CRI	Ra> 90
Beam Angle	70°
Colour temperature	2700k/3000K/4000K/5000K 2500k/2700K/3500K/4500K

System luminous efficacy up to 94lm/W



Model	CCT	CRI 90+	Beam Angle	Lumen	Efficacy	Lumen	Efficacy
DL50-25-XX-01	2700K		70°	2063lm	85.2lm/W	1775lm	72.3lm/W
DL50-25-XX-01	3000K		70°	2221lm	93.5lm/W	1879lm	79.2lm/W
DL50-25-XX-01	4000K		70°	2218lm	91.4lm/W	1870lm	77.2lm/W
DL50-25-XX-01	5000K		70°	2287lm	94lm/W	1907lm	79.3lm/W

Reflector



Model	CCT	CRI 90+	Beam Angle	Lumen	Efficacy
DL50-25-XX-01	2500K		70°	1816lm	74.8lm/W
DL50-25-XX-01	2700K		70°	1956lm	81.9lm/W
DL50-25-XX-01	3500K		70°	1943lm	79.5lm/W
DL50-25-XX-01	4500K		70°	1949lm	81lm/W

Reflector



## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS