




Cut-out: Ø200mm

Packaging

Box Dimensions	L250 x W250 x H185mm
Box Net Weight	1.97Kg
Box Gross Weight	2.33Kg
Carton Dimensions	L515 x W515 x H395 mm/8 PCS
Carton Net Weight	15.76Kg
Carton Gross Weight	19.67Kg

FEATURES

- Modular Design.
- System power up to 40W.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/850mA
Power	33.5W
Rated Input Current	0.1675A
PF value	>0.9
THD	<15%
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Non-dimmable with PHILIPS driver

Optical Data

LED Brand	Bridgelux SMD LED
CRI	Ra> 90
Beam Angle	70°
Colour temperature	2700k/3000K/4000K/5000K 2500k/2700K/3500K/4500K
System luminous efficacy up to	92.8lm/W



Model	CCT		Beam Angle	Lumen	Efficacy	Lumen	Efficacy
DL50-35-XX-01	2700K	CRI 90+	70°	2912lm	84.7lm/W	2382lm	68lm/W
DL50-35-XX-01	3000K		70°	3069lm	91lm/W	2517lm	73.4lm/W
DL50-35-XX-01	4000K		70°	3134lm	78.4lm/W	2560lm	73lm/W
DL50-35-XX-01	5000K		70°	3227lm	92.8lm/W	2609lm	74.6lm/W

Reflector



Model	CCT		Beam Angle	Lumen	Efficacy
DL50-35-XX-01	2500K	CRI 90+	70°	2571lm	74.7lm/W
DL50-35-XX-01	2700K		70°	2671lm	79.4lm/W
DL50-35-XX-01	3500K		70°	2696lm	78.4lm/W
DL50-35-XX-01	4500K		70°	2719lm	79.7lm/W

Reflector



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS