



Cut-out: Ø150mm

FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable beam.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/600mA
Power	25W
Rated Input Current	0.125A
PF value	>0.9
THD	<6%
Ingress Protection	IP54
Operating Temperature	-10—40℃
Dimmability	Non-dimmable with PHILIPS driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperature	2700k/3000K/4000K
System luminous efficacy up to	100.7lm/W

Packaging

Box Dimensions	L210 x W210 x H145mm
Box Net Weight	1.2Kg
Box Gross Weight	1.41Kg
Carton Dimensions	L435 x W435 x H460 mm/12 PCS
Carton Net Weight	14.4Kg
Carton Gross Weight	17.72Kg



Model	CCT		Beam Angle	Lumen	Efficacy
DL51-25-XX-01	2700K	CRI 90+	15°	2141lm	88.4lm/W
			24°	2050lm	84.7lm/W
			36°	2151lm	88.6lm/W
			60°	2137lm	88.3lm/W
DL51-25-XX-01	3000K		15°	2295lm	96.4lm/W
			24°	2193lm	92lm/W
			36°	2324lm	96.7lm/W
			60°	2276lm	95.5lm/W
DL51-25-XX-01	4000K		15°	2432lm	100.6lm/W
			24°	2358lm	97.4lm/W
			36°	2451lm	101.4lm/W
			60°	2454lm	100.7lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS