


6W 9W
POWER



Black / White



Packaging

Box Dimensions	L175 x W165 x H145mm
Box Net Weight	0.72Kg
Box Gross Weight	0.96Kg
Carton Dimensions	L540 x W510 x H315 mm/18 PCS
Carton Net Weight	12.96Kg
Carton Gross Weight	17.98Kg

FEATURES

- Maximum 45° vertical rotation can be created on the main body.
- Optic interchangeable.
- Power selectable.
- Flicker-free internal driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/210mA(9W) DC33V/145mA(6W)
Power	9W 6W
Rated Input Current	0.045A
THD	<25%(9W) <35%(6W)
PF value	>0.9(9W) >0.8(6W)
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 90
Beam Angle	10°/20°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	98lm/W



RoHS CE



Model	CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
DL52-09-XX-01	2700K	10°	457lm	73lm/W	10°	753lm	84lm/W
		20°	513lm	82lm/W	20°	698lm	78lm/W
		36°	525lm	84lm/W	36°	792lm	89lm/W
		60°	520lm	83lm/W	60°	746lm	84lm/W
DL52-09-XX-01	3000K	10°	448lm	71lm/W	10°	781lm	88lm/W
		20°	474lm	76lm/W	20°	717lm	81lm/W
		36°	546lm	87lm/W	36°	786lm	88lm/W
		60°	536lm	86lm/W	60°	773lm	87lm/W
DL52-09-XX-01	4000K	10°	544lm	87lm/W	10°	778lm	88lm/W
		20°	587lm	94lm/W	20°	726lm	82lm/W
		36°	610lm	98lm/W	36°	847lm	95lm/W
		60°	584lm	93lm/W	60°	827lm	93lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS