



Cut-out: Ø68mm-83mm

FEATURES

- Wide cutout range from 68mm to 83mm.
- Tilttable 30° and rotatable 355°.
- Insulation coverable directly.
- Easy loop in&out.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/240mA DC30-40V/230mA(DALI)
Power	10W
Rated Input Current	50mA
PF value	>0.7
THD	<30%
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver DALI dimmable with ACTEC driver
Lifespan L70/B50 at 25°C	>100000h
Lifespan L90/B10 at 25°C	>100000h

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
Beam Angle	36°/60°
Colour temperatures	1800K-3000K
System luminous efficacy up to	83lm/W

Packaging

Box Dimensions	L130 x W130 x H65 x T2mm
Box Net Weight	0.259Kg
Box Gross Weight	0.3Kg
Carton Dimensions	L405 x W275 x H350 mm/30 PCS
Carton Net Weight	7.77Kg
Carton Gross Weight	9.4Kg

Packaging(DALI)

Box Dimensions	L160 x W130 x H65 x T2mm
Box Net Weight	0.359Kg
Box Gross Weight	0.4Kg
Carton Dimensions	L405 x W335 x H350 mm/30 PCS
Carton Net Weight	10.77Kg
Carton Gross Weight	12.4Kg



CCT		Beam Angle	Lumen	Efficacy
1800K-3000K	10W	36°	802lm	83lm/W
		60°	799lm	82lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS