



Cut-out: Ø68mm/83mm

FEATURES

- Tiltable 30° and rotatable 355°.
- Insulation coverable directly.
- CCT changeable.
- Power selectable.
- Easy loop in&out.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/230mA(Max) DC30-40V/185mA(Min) DC30-40V/230mA(Max) (DALI) DC30-40V/180mA(Min) (DALI)
Power	10W(Max), 8W(Min)
Rated Input Current	50mA(Max), 40mA(Min)
PF value	>0.7
THD	<30%
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver DALI dimmable with ACTEC driver
Lifespan L70/B50 at 25°C	>100000h
Lifespan L90/B10 at 25°C	>100000h

Optical Data

LED Brand	ZMO
CRI	Ra>90
Beam Angle	36°/60°
Colour temperatures	2700K-3000K
System luminous efficacy up to	85lm/W

Packaging

Box Dimensions	L130 x W130 x H65 x T2mm
Box Net Weight	0.265Kg
Box Gross Weight	0.306Kg
Carton Dimensions	L405 x W275 x H350 mm/30 PCS
Carton Net Weight	7.95Kg
Carton Gross Weight	9.58Kg

Packaging(DALI)

Box Dimensions	L160 x W130 x H65 x T2mm
Box Net Weight	0.371Kg
Box Gross Weight	0.412Kg
Carton Dimensions	L405 x W335 x H350 mm/30 PCS
Carton Net Weight	11.13Kg
Carton Gross Weight	12.76Kg

RoHS

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	8W (Min)	36°	689lm	85lm/W	10W (Max)	36°	820lm	81lm/W
		60°	660lm	82lm/W		60°	796lm	78lm/W
3000K		36°	694lm	85lm/W		36°	827lm	81lm/W
		60°	670lm	83lm/W		60°	805lm	79lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS