



Cut-out: Ø83mm-90mm

FEATURES

- Tilttable 30° in all directions.
- Insulation coverable directly.
- Beam angle interchangeable.
- Honeycomb optional.
- Easy loop in&out.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/240mA DC30-40V/230mA(DALI)
Power	10W
Rated Input Current	50mA
PF value	>0.9
THD	<25%
Ingress Protection	IP65
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver DALI dimmable with ACTEC driver
Lifespan L70/B50 at 25°C	>100000H
Lifespan L90/B10 at 25°C	>100000H

Packaging

Box Dimensions	L130 x W130 x H75 x T2mm
Box Net Weight	0.369Kg
Box Gross Weight	0.422Kg
Carton Dimensions	L405 x W275 x H325 mm/24 PCS
Carton Net Weight	8.86Kg
Carton Gross Weight	10.5Kg

Packaging(DALI)

Box Dimensions	L160 x W130 x H75 x T2mm
Box Net Weight	0.473Kg
Box Gross Weight	0.535Kg
Carton Dimensions	L405 x W335 x H325 mm/24 PCS
Carton Net Weight	11.35Kg
Carton Gross Weight	13.4Kg

Accessories

	Honeycomb
	Lens(24°/38°/60°)
	Reflector(24°/38°/50°)

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
SDCM	≤3
Beam Angle	24°/38°/60°
Colour temperatures	1800K-3000K
System luminous efficacy up to	76lm/W



CCT		Beam Angle	Lumen	Efficacy
1800K-3000K	CRI 90+	24°	713lm	74lm/W
		38°	748lm	76lm/W
		60°	720lm	75lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS