



Cut-out: Ø83mm-90mm

FEATURES

- Tilttable 30° in all directions.
- Insulation coverable directly.
- Beam angle interchangeable.
- Honeycomb optional.
- Power selectable.
- Easy loop in&out.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/230mA(Max) DC30-40V/185mA(Min) DC30-40V/230mA(Max)(DALI) DC30-40V/180mA(Min)(DALI)
Power	10W(Max), 8W(Min)
Rated Input Current	50mA
PF value	>0.9
THD	<25%
Ingress Protection	IP65
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver DALI dimmable with ACTEC driver
Lifespan L70/B50 at 25°C	>100000H
Lifespan L90/B10 at 25°C	>100000H

Packaging

Box Dimensions	L130 x W130 x H75 x T2mm
Box Net Weight	0.369Kg
Box Gross Weight	0.422Kg
Carton Dimensions	L405 x W275 x H325 mm/24 PCS
Carton Net Weight	8.86Kg
Carton Gross Weight	10.5Kg

Packaging(DALI)

Box Dimensions	L160 x W130 x H75 x T2mm
Box Net Weight	0.473Kg
Box Gross Weight	0.535Kg
Carton Dimensions	L405 x W335 x H325 mm/24 PCS
Carton Net Weight	11.35Kg
Carton Gross Weight	13.4Kg

Accessories

	Honeycomb
	Lens(24°/38°/60°)
	Reflector(24°/38°/50°)

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90, Ra>97
SDCM	≤3
Beam Angle	24°/38°/60°
Colour temperatures	2700K/3000K/4000K 2700K/3000K(Ra>97)
System luminous efficacy up to	92lm/W



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

CCT			Beam Angle	Lumen	Efficacy	Beam Angle			Lumen	Efficacy
2700K	CRI 90+	10W Max	24°	760lm	77lm/W	8W Min	24°	616lm	79lm/W	
			38°	772lm	78lm/W		38°	633lm	81lm/W	
			60°	755lm	77lm/W		60°	615lm	79lm/W	
24°			821lm	82lm/W	24°		663lm	83lm/W		
38°			837lm	84lm/W	38°		687lm	86lm/W		
60°			829lm	83lm/W	60°		670lm	84lm/W		
4000K			24°	863lm	87lm/W		24°	697lm	89lm/W	
			38°	881lm	89lm/W		38°	722lm	92lm/W	
			60°	878lm	88lm/W		60°	708lm	90lm/W	

CCT			Beam Angle	Lumen	Efficacy	Beam Angle			Lumen	Efficacy	
2700K	CRI 97+	10W Max	24°	616lm	63lm/W	8W Min	24°	499lm	64lm/W		
			38°	628lm	64lm/W		38°	512lm	66lm/W		
			60°	618lm	63lm/W		60°	505lm	65lm/W		
3000K			24°	643lm	65lm/W		24°	522lm	67lm/W		
			38°	659lm	66lm/W		38°	546lm	70lm/W		
			60°	647lm	66lm/W		60°	530lm	68lm/W		

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS