



FEATURES

- Tiltable 30° in all directions.
- Insulation coverable directly.
- Beam angle interchangeable.
- Honeycomb optional.
- Power selectable.
- Easy loop in/out.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/230mA(Max) DC30-40V/185mA(Min) DC30-40V/230mA(Max)(DALI) DC30-40V/180mA(Min)(DALI)
Power	10W(Max), 8W(Min)
Rated Input Current	50mA
PF value	>0.9
THD	<25%
Ingress Protection	IP65
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver DALI dimmable with ACTEC driver
Lifespan L70/B50 at 25°C	>100000H
Lifespan L90/B10 at 25°C	>100000H

Packaging

Box Dimensions	L130 x W130 x H75 x T2mm
Box Net Weight	0.369Kg
Box Gross Weight	0.422Kg
Carton Dimensions	L405 x W275 x H325 mm/24 PCS
Carton Net Weight	8.86Kg
Carton Gross Weight	10.5Kg

Packaging(DALI)

Box Dimensions	L160 x W130 x H75 x T2mm
Box Net Weight	0.473Kg
Box Gross Weight	0.535Kg
Carton Dimensions	L405 x W335 x H325 mm/24 PCS
Carton Net Weight	11.35Kg
Carton Gross Weight	13.4Kg

Accessories

	Honeycomb
	Lens(24°/38°/60°)
	Reflector(24°/38°/50°)

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
SDCM	≤3
Beam Angle	24°/38°/50°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	80lm/W



CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	24°	710lm	72lm/W	24°	580lm	74lm/W
	38°	703lm	72lm/W	38°	575lm	74lm/W
	50°	635lm	65lm/W	50°	518lm	66lm/W
3000K	24°	773lm	78lm/W	24°	633lm	80lm/W
	38°	763lm	77lm/W	38°	624lm	79lm/W
	50°	687lm	69lm/W	50°	561lm	71lm/W
4000K	24°	772lm	78lm/W	24°	631lm	80lm/W
	38°	761lm	77lm/W	38°	621lm	79lm/W
	50°	683lm	69lm/W	50°	557lm	71lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS