



Packaging

Box Dimensions	L130 x W130 x H92 mm
Box Net Weight	0.200Kg
Box Gross Weight	0.251Kg
Carton Dimensions	L420 x W405 x H390 mm/60 PCS
Carton Net Weight	12.02Kg
Carton Gross Weight	15.05Kg

FEATURES

- Heat sink design better for air convection, good heat dissipation.
- Bridgelux COB LED, up to 68 lm/W, CRI 90+.
- Fit in most of MR11 LED downlight converter.
- Dimming capability. 1. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco; 2. DALI dimming.
- The driver with CE, RCM and SAA certification.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC18V/270mA
Power	6W
Rated Input Current	0.03A
PF value	>0.82
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
Beam Angle	24°
Colour temperatures	1800K-3000K
System luminous efficacy up to	68lm/W



CCT		Beam Angle	Lumen	Efficacy
3000K	CRI 90+	24°	386lm	68lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS