




Black / White




FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC35V/400mA
Power	18W
Rated Input Current	0.075A
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	DALI
L70/B50 at 25°C	>200000H
L90/B10 at 25°C	>21000H



Packaging

Box Dimensions	L190 x W105 x H170 x T2mm
Box Net Weight	0.7Kg
Box Gross Weight	0.83Kg
Carton Dimensions	L545 x W395 x H360 mm/20 PCS
Carton Net Weight	14Kg
Carton Gross Weight	18Kg

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<6
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K-6500K
System luminous efficacy up to	85lm/W

Accessories

	GTS-BD01	Barn door
	GTS-ST01	45° Snoot
	HC05	Honeycomb
	GTS-OL01	Linear spread lens
	GTS-TWW01	Wallwash lens



CCT		Beam Angle	Lumen	Efficacy
2700K	CRI 90+	15°	1283lm	70lm/W
		24°	1249lm	68lm/W
		36°	1220lm	66lm/W
		60°	1332lm	72lm/W
6500K		15°	1494lm	81lm/W
		24°	1467lm	80lm/W
		36°	1435lm	78lm/W
		60°	1572lm	85lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS