



FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC36V/1070mA(45W) DC36V/950mA(40W)
Power	45W 40W
Rated Input Current	0.187A(45W) 0.167A(40W)
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver
L70/B50 at 25°C	>160000H
L90/B10 at 25°C	>19000H

Packaging

Box Dimensions	L300 x W205 x H210 x T3mm
Box Net Weight	2.6Kg
Box Gross Weight	2.93Kg
Carton Dimensions	L630 x W520 x H230 mm/5 PCS
Carton Net Weight	13Kg
Carton Gross Weight	16.8Kg

Accessories

	GTL-BD01	Barn door
	GTL-ST01	45° Snoot
	HC07	Honeycomb
	GTL-OL01	Linear spread lens
	GTL-TWW01	Wallwash lens

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<6
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	107lm/W



CCT		Power	Beam Angle	Lumen	Efficacy	Power	Beam Angle	Lumen	Efficacy
2700K	CRI 90+	40W	15°	3788lm	96lm/W	45W	15°	4071lm	92lm/W
			24°	3894lm	99lm/W		24°	4197lm	95lm/W
			36°	3948lm	100lm/W		36°	4279lm	97lm/W
			60°	3917lm	100lm/W		60°	4257lm	97lm/W
3000K			15°	3603lm	91lm/W		15°	4022lm	89lm/W
			24°	3712lm	95lm/W		24°	4066lm	92lm/W
			36°	3753lm	96lm/W		36°	4146lm	94lm/W
			60°	3738lm	96lm/W		60°	4102lm	93lm/W
4000K			15°	3972lm	102lm/W		15°	4454lm	100lm/W
			24°	4100lm	105lm/W		24°	4514lm	103lm/W
			36°	4133lm	107lm/W		36°	4589lm	105lm/W
			60°	4120lm	107lm/W		60°	4542lm	104lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS