



FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC36V/850mA(35W) DC36V/740mA(30W)
Power	35W 30W
Rated Input Current	0.145A(35W) 0.125A(30W)
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	DALI
L70/B50 at 25°C	>160000H
L90/B10 at 25°C	>103000H

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	120lm/W

Packaging

Box Dimensions	L235 x W155 x H185 x T3mm
Box Net Weight	1.5Kg
Box Gross Weight	1.72Kg
Carton Dimensions	L485 x W405 x H390 mm/10 PCS
Carton Net Weight	15Kg
Carton Gross Weight	18.6Kg

Accessories

	GTM-BD01	Barn door
	GTM-ST01	45° Snoot
	HC06	Honeycomb
	GTM-OL01	Linear spread lens
	GTM-TWW01	Wallwash lens



CCT		Power	Beam Angle	Lumen	Efficacy	Power	Beam Angle	Lumen	Efficacy
2700K	CRI 90+	30W	15°	3190lm	106lm/W	35W	15°	3597lm	102lm/W
			24°	3203lm	106lm/W		24°	3595lm	102lm/W
			36°	3433lm	114lm/W		36°	3830lm	109lm/W
			60°	3378lm	112lm/W		60°	3807lm	108lm/W
3000K			15°	3195lm	106lm/W		15°	3549lm	101lm/W
			24°	3203lm	106lm/W		24°	3567lm	102lm/W
			36°	3406lm	113lm/W		36°	3800lm	108lm/W
			60°	3387lm	113lm/W		60°	3776lm	108lm/W
4000K			15°	3343lm	111lm/W		15°	3722lm	106lm/W
			24°	3357lm	112lm/W		24°	3738lm	107lm/W
			36°	3596lm	120lm/W		36°	4025lm	115lm/W
			60°	3543lm	118lm/W		60°	3944lm	113lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS