



## FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

## Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC36V/1100mA(45W) DC36V/980mA(40W)
Power	45W   40W
Rated Input Current	0.187A(45W)   0.167A(40W)
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	DALI
L70/B50 at 25°C	>160000H
L90/B10 at 25°C	>103000H

## Packaging

Box Dimensions	L300 x W205 x H210 x T3mm
Box Net Weight	2.6Kg
Box Gross Weight	2.93Kg
Carton Dimensions	L630 x W520 x H230 mm/5 PCS
Carton Net Weight	13Kg
Carton Gross Weight	16.8Kg

## Accessories

	GTL-BD01	Barn door
	GTL-ST01	45° Snoot
	HC07	Honeycomb
	GTL-OL01	Linear spread lens
	GTL-TWW01	Wallwash lens

## LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	110lm/W



CCT	Power				Beam Angle	Lumen	Efficacy	Power	Beam Angle	Lumen	Efficacy
2700K	CRI 90+	40W	15°	3887lm	98lm/W	45W	15°	4178lm	94lm/W		
			24°	3952lm	99lm/W		24°	4280lm	96lm/W		
			36°	4031lm	101lm/W		36°	4373lm	98lm/W		
			60°	4048lm	102lm/W		60°	4386lm	98lm/W		
3000K			15°	3804lm	95lm/W		15°	4473lm	101lm/W		
			24°	3870lm	97lm/W		24°	4588lm	103lm/W		
			36°	3945lm	98lm/W		36°	4734lm	107lm/W		
			60°	3953lm	99lm/W		60°	4700lm	106lm/W		
4000K			15°	4153lm	105lm/W		15°	4498lm	101lm/W		
			24°	4246lm	107lm/W		24°	4588lm	104lm/W		
			36°	4339lm	110lm/W		36°	4692lm	106lm/W		
			60°	4346lm	110lm/W		60°	4707lm	106lm/W		

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS