



FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC36V/840mA(35W) DC36V/750mA(30W)
Power	35W 30W
Rated Input Current	0.146A(35W) 0.125A(30W)
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver
L70/B50 at 25°C	>160000H
L90/B10 at 25°C	>19000H

Packaging

Box Dimensions	L235 x W155 x H185 x T3mm
Box Net Weight	1.5Kg
Box Gross Weight	1.72Kg
Carton Dimensions	L485 x W405 x H390 mm/10 PCS
Carton Net Weight	15Kg
Carton Gross Weight	18.6Kg

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<6
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	117lm/W

Accessories

	GTM-BD01	Barn door
	GTM-ST01	45° Snoot
	HC06	Honeycomb
	GTM-OL01	Linear spread lens
	GTM-TWW01	Wallwash lens



CCT		Power	Beam Angle	Lumen	Efficacy	Power	Beam Angle	Lumen	Efficacy
2700K	CRI 90+	30W	15°	3079lm	104lm/W	35W	15°	3382lm	99lm/W
			24°	3080lm	104lm/W		24°	3404lm	99lm/W
			36°	3183lm	108lm/W		36°	3531lm	103lm/W
			60°	3239lm	110lm/W		60°	3608lm	106lm/W
3000K			15°	3021lm	103lm/W		15°	3517lm	102lm/W
			24°	3044lm	104lm/W		24°	3495lm	101lm/W
			36°	3182lm	109lm/W		36°	3644lm	106lm/W
			60°	3223lm	111lm/W		60°	3672lm	108lm/W
4000K			15°	3286lm	111lm/W		15°	3614lm	106lm/W
			24°	3271lm	111lm/W		24°	3615lm	106lm/W
			36°	3394lm	116lm/W		36°	3762lm	111lm/W
			60°	3434lm	117lm/W		60°	3819lm	113lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS