



Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.215Kg
Box Gross Weight	0.272Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	8.6Kg
Carton Gross Weight	10.88Kg

FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/130mA
Power	6W
Rated Input Current	0.03A
THD	<35%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Sunlike COB LED
CRI	Ra> 97
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	122lm/W



Model	CCT	Beam Angle	Lumen	Efficacy
MD10-06-SL-03	2700K	15°	396lm	66lm/W
		24°	399lm	66lm/W
		36°	398lm	66lm/W
		60°	401lm	67lm/W
MD10-06-SL-03	3000K	15°	406lm	68lm/W
		24°	411lm	69lm/W
		36°	408lm	69lm/W
		60°	414lm	70lm/W
MD10-06-SL-03	4000K	15°	420lm	71lm/W
		24°	428lm	72lm/W
		36°	424lm	72lm/W
		60°	427lm	72lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS