



Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.226Kg
Box Gross Weight	0.283Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	9.04Kg
Carton Gross Weight	11.32Kg

FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/130mA
Power	6W
Rated Input Current	0.03A
THD	<6%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	125lm/W



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K		15°	597lm	108lm/W		15°	482lm	87lm/W
		24°	631lm	114lm/W		24°	514lm	93lm/W
		36°	626lm	113lm/W		36°	510lm	92lm/W
		60°	609lm	110lm/W		60°	497lm	90lm/W
3000K	CRI 80+	15°	630lm	112lm/W	CRI 90+	15°	532lm	96lm/W
		24°	640lm	116lm/W		24°	545lm	98lm/W
		36°	638lm	115lm/W		36°	548lm	99lm/W
		60°	620lm	111lm/W		60°	526lm	95lm/W
4000K		15°	663lm	120lm/W		15°	574lm	105lm/W
		24°	689lm	125lm/W		24°	580lm	106lm/W
		36°	680lm	121lm/W		36°	577lm	105lm/W
		60°	650lm	118lm/W		60°	570lm	104lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS