



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/130mA
Power	6W
Rated Input Current	0.03A
THD	<6%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80, Ra > 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	114lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.217Kg
Box Gross Weight	0.274Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	8.68Kg
Carton Gross Weight	10.96Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	613lm	111lm/W	CRI 90+	15°	493lm	89lm/W
		25°	611lm	109lm/W		25°	488lm	88lm/W
		38°	615lm	110lm/W		38°	491lm	88lm/W
		60°	611lm	109lm/W		60°	485lm	88lm/W
3000K		15°	620lm	111lm/W		15°	527lm	95lm/W
		25°	619lm	112lm/W		25°	526lm	96lm/W
		38°	620lm	112lm/W		38°	527lm	96lm/W
		60°	615lm	111lm/W		60°	523lm	95lm/W
4000K		15°	627lm	113lm/W		15°	565lm	103lm/W
		25°	634lm	114lm/W		25°	556lm	101lm/W
		38°	631lm	114lm/W		38°	567lm	103lm/W
		60°	625lm	113lm/W		60°	559lm	100lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS