



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/130mA
Power	6W
Rated Input Current	0.03A
THD	<35%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	122lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.215Kg
Box Gross Weight	0.272Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	8.6Kg
Carton Gross Weight	10.88Kg



Model	CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
MD10-06-XX-03	2700K	15°	595lm	108lm/W	15°	485lm	87lm/W
		24°	611lm	111lm/W	24°	492lm	89lm/W
		36°	606lm	110lm/W	36°	493lm	89lm/W
		60°	619lm	112lm/W	60°	500lm	90lm/W
MD10-06-XX-03	3000K	15°	600lm	108lm/W	15°	514lm	93lm/W
		24°	618lm	112lm/W	24°	528lm	95lm/W
		36°	616lm	111lm/W	36°	526lm	95lm/W
		60°	627lm	113lm/W	60°	533lm	96lm/W
MD10-06-XX-03	4000K	15°	658lm	118lm/W	15°	562lm	101lm/W
		24°	677lm	122lm/W	24°	574lm	104lm/W
		36°	670lm	121lm/W	36°	567lm	103lm/W
		60°	674lm	122lm/W	60°	574lm	104lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Reuil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS