



Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.234Kg
Box Gross Weight	0.291Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	9.36Kg
Carton Gross Weight	11.64Kg

FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/130mA
Power	6W
Rated Input Current	0.03A
THD	<6%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80, Ra > 90
Beam Angle	38°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	105lm/W



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	38°	555lm	100lm/W	CRI 90+	38°	459lm	83lm/W
3000K		38°	556lm	100lm/W		38°	476lm	86lm/W
4000K		38°	582lm	105lm/W		38°	502lm	91lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS