



Indoor Luminaire Photometric Data

Description Information

Luminary Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2020/01/05
Manufacture: Shenzhen Norming Lighting Co., Ltd	Shld.Ang(°):	Test Machine:GON-2000
Test Lab: QUality peatment	Frequency (Hz):	Lamp CCT(K): Ra:
Lum. Size (W*L*H): 0.498m*0.498m*0.060m	Lum. Area (m2): 0.278	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 458.840	Luminary Flux(lm): 458.837	Field Angle(10%Imax): 63.5(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 447.851lm 97.61%
Rated Voltage(V):	Luminary EER(lm/W): 83.379	Up Lumens&Percent: 10.986lm 2.39%
Tested Power(W): 5.503	Max. Candela(cd): 926.955	S/MH: C0_a180=0.639 C90_270=0.641
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=2.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf): 240.4, 0.026, 0.867	Beam Angle(50%Imax): 38.7(°)	ErP Φ use(90°): 412.590lm
Lamp Size (W*L*H): 0.498m*0.498m*0.060m	Left=-17.5°, Right=21.1°	IRF(%): 420.350



2D Plane Light Intensity Distribution Curve

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05




IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

3D Light Intensity Distribution Modal

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.88	0.88	0.19	0.19	47.0-48.0	1.26	422.47	0.28	92.07
1.0-2.0	2.65	3.53	0.58	0.77	48.0-49.0	1.21	423.68	0.26	92.34
2.0-3.0	4.39	7.92	0.96	1.73	49.0-50.0	1.16	424.84	0.25	92.59
3.0-4.0	6.10	14.03	1.33	3.06	50.0-51.0	1.11	425.95	0.24	92.83
4.0-5.0	7.77	21.80	1.69	4.75	51.0-52.0	1.07	427.02	0.23	93.07
5.0-6.0	9.38	31.17	2.04	6.79	52.0-53.0	1.03	428.05	0.23	93.29
6.0-7.0	10.90	42.07	2.37	9.17	53.0-54.0	1.00	429.05	0.22	93.51
7.0-8.0	12.31	54.38	2.68	11.85	54.0-55.0	0.96	430.01	0.21	93.72
8.0-9.0	13.62	68.00	2.97	14.82	55.0-56.0	0.92	430.93	0.20	93.92
9.0-10.0	14.79	82.78	3.22	18.04	56.0-57.0	0.89	431.82	0.19	94.11
10.0-11.0	15.80	98.58	3.44	21.49	57.0-58.0	0.86	432.69	0.19	94.30
11.0-12.0	16.66	115.24	3.63	25.12	58.0-59.0	0.83	433.52	0.18	94.48
12.0-13.0	17.36	132.60	3.78	28.90	59.0-60.0	0.81	434.33	0.18	94.66
13.0-14.0	17.89	150.49	3.90	32.80	60.0-61.0	0.78	435.11	0.17	94.83
14.0-15.0	18.23	168.72	3.97	36.77	61.0-62.0	0.76	435.87	0.17	94.99
15.0-16.0	18.37	187.09	4.00	40.78	62.0-63.0	0.74	436.61	0.16	95.15
16.0-17.0	18.29	205.38	3.99	44.76	63.0-64.0	0.71	437.32	0.15	95.31
17.0-18.0	17.98	223.36	3.92	48.68	64.0-65.0	0.68	438.00	0.15	95.46
18.0-19.0	17.47	240.83	3.81	52.49	65.0-66.0	0.66	438.66	0.14	95.60
19.0-20.0	16.76	257.59	3.65	56.14	66.0-67.0	0.63	439.29	0.14	95.74
20.0-21.0	15.85	273.44	3.46	59.59	67.0-68.0	0.61	439.89	0.13	95.87
21.0-22.0	14.82	288.26	3.23	62.82	68.0-69.0	0.58	440.47	0.13	96.00
22.0-23.0	13.71	301.97	2.99	65.81	69.0-70.0	0.56	441.03	0.12	96.12
23.0-24.0	12.55	314.52	2.74	68.55	70.0-71.0	0.53	441.56	0.12	96.23
24.0-25.0	11.38	325.90	2.48	71.03	71.0-72.0	0.51	442.07	0.11	96.35
25.0-26.0	10.25	336.15	2.23	73.26	72.0-73.0	0.49	442.56	0.11	96.45
26.0-27.0	9.20	345.35	2.01	75.27	73.0-74.0	0.47	443.03	0.10	96.55
27.0-28.0	8.27	353.62	1.80	77.07	74.0-75.0	0.44	443.47	0.10	96.65
28.0-29.0	7.46	361.08	1.63	78.69	75.0-76.0	0.42	443.89	0.09	96.74
29.0-30.0	6.74	367.82	1.47	80.16	76.0-77.0	0.40	444.30	0.09	96.83
30.0-31.0	6.12	373.94	1.33	81.50	77.0-78.0	0.38	444.68	0.08	96.91
31.0-32.0	5.55	379.49	1.21	82.71	78.0-79.0	0.36	445.04	0.08	96.99
32.0-33.0	5.04	384.53	1.10	83.80	79.0-80.0	0.34	445.38	0.07	97.07
33.0-34.0	4.57	389.10	1.00	84.80	80.0-81.0	0.32	445.71	0.07	97.14
34.0-35.0	4.14	393.24	0.90	85.70	81.0-82.0	0.30	446.01	0.07	97.20
35.0-36.0	3.75	396.99	0.82	86.52	82.0-83.0	0.29	446.30	0.06	97.27
36.0-37.0	3.40	400.39	0.74	87.26	83.0-84.0	0.27	446.56	0.06	97.32
37.0-38.0	3.10	403.48	0.68	87.94	84.0-85.0	0.25	446.82	0.05	97.38
38.0-39.0	2.83	406.31	0.62	88.55	85.0-86.0	0.23	447.05	0.05	97.43
39.0-40.0	2.57	408.88	0.56	89.11	86.0-87.0	0.22	447.27	0.05	97.48
40.0-41.0	2.34	411.22	0.51	89.62	87.0-88.0	0.20	447.47	0.04	97.52
41.0-42.0	2.11	413.33	0.46	90.08	88.0-89.0	0.19	447.66	0.04	97.56
42.0-43.0	1.89	415.22	0.41	90.49	89.0-90.0	0.19	447.85	0.04	97.61
43.0-44.0	1.70	416.92	0.37	90.86	90.0-91.0	0.18	448.03	0.04	97.64
44.0-45.0	1.54	418.46	0.34	91.20	91.0-92.0	0.18	448.21	0.04	97.68
45.0-46.0	1.42	419.88	0.31	91.51	92.0-93.0	0.17	448.38	0.04	97.72
46.0-47.0	1.33	421.21	0.29	91.80	93.0-94.0	0.17	448.55	0.04	97.76

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.16	448.71	0.04	97.79	141.0-142.0	0.15	454.79	0.03	99.12
95.0-96.0	0.16	448.87	0.03	97.83	142.0-143.0	0.16	454.95	0.03	99.15
96.0-97.0	0.16	449.03	0.03	97.86	143.0-144.0	0.16	455.10	0.03	99.19
97.0-98.0	0.15	449.19	0.03	97.90	144.0-145.0	0.16	455.26	0.03	99.22
98.0-99.0	0.15	449.34	0.03	97.93	145.0-146.0	0.16	455.42	0.03	99.25
99.0-100.0	0.15	449.48	0.03	97.96	146.0-147.0	0.16	455.58	0.03	99.29
100.0-101.0	0.14	449.63	0.03	97.99	147.0-148.0	0.16	455.74	0.03	99.32
101.0-102.0	0.14	449.77	0.03	98.02	148.0-149.0	0.16	455.90	0.03	99.36
102.0-103.0	0.14	449.91	0.03	98.05	149.0-150.0	0.16	456.05	0.03	99.39
103.0-104.0	0.14	450.04	0.03	98.08	150.0-151.0	0.16	456.21	0.03	99.43
104.0-105.0	0.13	450.17	0.03	98.11	151.0-152.0	0.16	456.37	0.03	99.46
105.0-106.0	0.13	450.30	0.03	98.14	152.0-153.0	0.15	456.52	0.03	99.49
106.0-107.0	0.13	450.43	0.03	98.17	153.0-154.0	0.15	456.67	0.03	99.53
107.0-108.0	0.13	450.56	0.03	98.19	154.0-155.0	0.15	456.82	0.03	99.56
108.0-109.0	0.12	450.68	0.03	98.22	155.0-156.0	0.15	456.97	0.03	99.59
109.0-110.0	0.12	450.80	0.03	98.25	156.0-157.0	0.14	457.11	0.03	99.62
110.0-111.0	0.12	450.92	0.03	98.27	157.0-158.0	0.14	457.25	0.03	99.65
111.0-112.0	0.12	451.04	0.03	98.30	158.0-159.0	0.13	457.38	0.03	99.68
112.0-113.0	0.12	451.15	0.03	98.33	159.0-160.0	0.13	457.51	0.03	99.71
113.0-114.0	0.11	451.27	0.03	98.35	160.0-161.0	0.12	457.63	0.03	99.74
114.0-115.0	0.11	451.38	0.02	98.37	161.0-162.0	0.12	457.75	0.03	99.76
115.0-116.0	0.11	451.50	0.02	98.40	162.0-163.0	0.11	457.87	0.02	99.79
116.0-117.0	0.11	451.61	0.02	98.42	163.0-164.0	0.11	457.98	0.02	99.81
117.0-118.0	0.11	451.72	0.02	98.45	164.0-165.0	0.10	458.08	0.02	99.83
118.0-119.0	0.11	451.83	0.02	98.47	165.0-166.0	0.10	458.17	0.02	99.85
119.0-120.0	0.11	451.94	0.02	98.50	166.0-167.0	0.09	458.26	0.02	99.87
120.0-121.0	0.11	452.05	0.02	98.52	167.0-168.0	0.08	458.35	0.02	99.89
121.0-122.0	0.11	452.17	0.02	98.55	168.0-169.0	0.08	458.42	0.02	99.91
122.0-123.0	0.11	452.28	0.02	98.57	169.0-170.0	0.07	458.50	0.02	99.92
123.0-124.0	0.11	452.39	0.02	98.59	170.0-171.0	0.06	458.56	0.01	99.94
124.0-125.0	0.11	452.51	0.03	98.62	171.0-172.0	0.06	458.62	0.01	99.95
125.0-126.0	0.12	452.62	0.03	98.65	172.0-173.0	0.05	458.67	0.01	99.96
126.0-127.0	0.12	452.74	0.03	98.67	173.0-174.0	0.04	458.71	0.01	99.97
127.0-128.0	0.12	452.86	0.03	98.70	174.0-175.0	0.04	458.75	0.01	99.98
128.0-129.0	0.12	452.98	0.03	98.72	175.0-176.0	0.03	458.78	0.01	99.99
129.0-130.0	0.12	453.11	0.03	98.75	176.0-177.0	0.02	458.81	0.01	99.99
130.0-131.0	0.13	453.23	0.03	98.78	177.0-178.0	0.02	458.82	0.00	100.00
131.0-132.0	0.13	453.36	0.03	98.81	178.0-179.0	0.01	458.83	0.00	100.00
132.0-133.0	0.13	453.49	0.03	98.83	179.0-180.0	0.00	458.84	0.00	100.00
133.0-134.0	0.13	453.63	0.03	98.86					
134.0-135.0	0.14	453.77	0.03	98.89					
135.0-136.0	0.14	453.90	0.03	98.92					
136.0-137.0	0.14	454.05	0.03	98.96					
137.0-138.0	0.14	454.19	0.03	98.99					
138.0-139.0	0.15	454.34	0.03	99.02					
139.0-140.0	0.15	454.49	0.03	99.05					
140.0-141.0	0.15	454.64	0.03	99.08					

Rectangle ISO Lighting Intensity Diagram

Lum. Name:MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05




IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Plane ISO-Illuminance Diagram

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00

Working Plane Maximum Illuminance(lx): 102.84

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0


IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

3D Plane ISO Illuminance Diagram

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

Space ISO Illuminance Curve



Curves:

[Unit: lx]

[EMax] =925.588

— [EMax*90%]=833.029

— [EMax*80%]=740.470

— [EMax*70%]=647.912

— [EMax*60%]=555.353

— [EMax*50%]=462.794

— [EMax*40%]=370.235

— [EMax*30%]=277.676

— [EMax*20%]=185.118

— [EMax*10%]=92.559

Space Plane Maximum Illuminance and @Angle:925.59lx,1.0deg

Plane Maximum Lighting Intensity and @Angle:926.955cd,0deg


IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Illuminance-Distance Diagram

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

Illuminance-Distance Curve



IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Indoor Luminance Limiting Curves

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	122	90	77	69	66	64	66	76	113
C90	101	77	66	60	56	53	53	58	80

Luminance Limiting Curve




Luminous Size: Length(m)=0.498 Width(m)=0.498 Height(m)=0.060 Area(m^2)=0.277884
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Indoor Budgetary Estimate Table

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Indoor Coefficient of Utilization Table

Lum. Name: MD10-06-XX-05 2700K RA90 38D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2020/01/05

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	118	118	118	118	115	115	115	115	110	110	110	105	105	105	100	100	100	98
1	113	110	108	106	110	108	106	104	103	102	100	99	98	97	95	94	93	91
2	108	103	99	96	105	101	98	95	98	95	92	94	92	90	91	89	88	86
3	103	97	92	88	101	95	91	88	92	89	86	90	87	84	87	85	83	81
4	98	91	86	82	96	90	85	82	88	84	80	85	82	79	83	81	78	77
5	94	86	81	77	92	85	80	77	83	79	76	82	78	75	80	77	74	73
6	90	82	77	73	89	81	76	72	80	75	72	78	74	71	77	73	70	69
7	87	78	73	69	85	77	72	69	76	71	68	75	71	68	73	70	67	66
8	83	75	69	66	82	74	69	65	73	68	65	72	68	65	71	67	64	63
9	80	71	66	63	79	71	66	62	70	65	62	69	65	62	68	64	61	60
10	77	68	63	60	76	68	63	60	67	62	59	66	62	59	65	62	59	58

Unified Glare Rating Table

Table with 3 columns: Lum. Name, Lum. Catalog, Test ID; Lamp Name, Lamp Catalog, Test Lab; Manufacture, Test Machine, Test Date.

Unified Glare Rating Table

Table with 11 columns for room surfaces (Ceiling, Wall, Floor) and room sizes (X, Y) at various heights (H), and a section for variations with observer position at spacings (S).

to the CIE Pub. 117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	924.39	924.39	924.39	924.39
γ 1.0	926.01	925.16	919.26	922.78
γ 2.0	926.96	923.60	911.49	918.98
γ 3.0	925.66	921.78	901.17	912.94
γ 4.0	923.70	917.80	887.52	904.81
γ 5.0	918.86	909.61	870.06	894.44
γ 6.0	910.19	900.77	851.22	880.92
γ 7.0	899.74	887.31	828.41	863.10
γ 8.0	885.68	872.59	803.45	840.94
γ 9.0	868.96	855.88	777.32	816.02
γ 10.0	849.09	834.20	746.18	787.93
γ 11.0	827.24	810.57	713.51	756.10
γ 12.0	802.77	783.99	679.76	722.43
γ 13.0	776.45	754.61	644.46	686.31
γ 14.0	747.56	722.47	608.80	649.05
γ 15.0	715.71	686.46	571.46	610.97
γ 16.0	679.50	647.22	531.64	572.39
γ 17.0	641.14	604.57	487.83	532.46
γ 18.0	600.33	562.76	443.03	489.98
γ 19.0	558.43	518.18	398.57	445.72
γ 20.0	514.49	472.34	353.99	400.64
γ 21.0	469.08	425.24	309.98	356.66
γ 22.0	424.58	378.49	270.40	314.83
γ 23.0	379.14	334.01	234.47	277.30
γ 24.0	334.33	293.08	201.89	242.16
γ 25.0	293.28	255.75	173.74	207.80
γ 26.0	256.18	222.21	150.87	176.76
γ 27.0	222.82	192.19	131.93	151.63
γ 28.0	194.07	167.19	115.72	131.20
γ 29.0	169.68	146.51	101.31	114.45
γ 30.0	149.22	128.87	88.77	100.46
γ 31.0	131.75	114.04	77.64	88.39
γ 32.0	116.22	101.13	67.90	78.03
γ 33.0	102.65	89.53	59.56	69.08
γ 34.0	90.75	79.14	52.39	61.10
γ 35.0	79.85	69.61	46.21	54.05
γ 36.0	70.57	61.35	40.86	48.03
γ 37.0	62.55	54.59	36.22	42.91
γ 38.0	55.51	48.70	32.22	38.55
γ 39.0	49.50	43.57	28.44	34.65
γ 40.0	44.20	38.94	24.86	31.07
γ 41.0	39.52	34.43	21.58	27.69
γ 42.0	35.38	30.14	18.80	24.30
γ 43.0	31.41	25.99	16.78	21.41
γ 44.0	27.49	22.44	15.43	19.18
γ 45.0	23.99	19.75	14.42	17.60
γ 46.0	21.39	17.96	13.58	16.43

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	19.54	16.66	12.85	15.46
γ 48.0	18.17	15.59	12.20	14.62
γ 49.0	17.02	14.64	11.60	13.86
γ 50.0	16.02	13.78	11.06	13.18
γ 51.0	15.10	13.00	10.55	12.52
γ 52.0	14.28	12.32	10.10	11.96
γ 53.0	13.58	11.68	9.64	11.41
γ 54.0	12.88	11.10	9.19	10.87
γ 55.0	12.26	10.52	8.79	10.35
γ 56.0	11.67	9.98	8.39	9.87
γ 57.0	11.09	9.48	8.04	9.44
γ 58.0	10.56	9.07	7.73	9.06
γ 59.0	10.08	8.65	7.45	8.71
γ 60.0	9.64	8.30	7.18	8.42
γ 61.0	9.25	7.95	6.90	8.12
γ 62.0	8.88	7.61	6.59	7.83
γ 63.0	8.51	7.27	6.30	7.50
γ 64.0	8.14	6.89	6.02	7.19
γ 65.0	7.75	6.53	5.75	6.89
γ 66.0	7.38	6.21	5.48	6.61
γ 67.0	7.02	5.90	5.22	6.33
γ 68.0	6.70	5.59	4.97	6.07
γ 69.0	6.38	5.30	4.75	5.81
γ 70.0	6.09	5.02	4.51	5.55
γ 71.0	5.80	4.75	4.28	5.30
γ 72.0	5.52	4.50	4.07	5.06
γ 73.0	5.26	4.25	3.85	4.83
γ 74.0	5.00	4.01	3.65	4.60
γ 75.0	4.76	3.79	3.44	4.38
γ 76.0	4.52	3.57	3.25	4.16
γ 77.0	4.29	3.36	3.06	3.95
γ 78.0	4.08	3.16	2.88	3.75
γ 79.0	3.87	2.97	2.70	3.55
γ 80.0	3.66	2.78	2.52	3.35
γ 81.0	3.46	2.60	2.35	3.16
γ 82.0	3.28	2.43	2.18	2.98
γ 83.0	3.10	2.26	2.03	2.80
γ 84.0	2.91	2.10	1.87	2.63
γ 85.0	2.73	1.94	1.72	2.44
γ 86.0	2.57	1.79	1.59	2.28
γ 87.0	2.40	1.65	1.49	2.14
γ 88.0	2.25	1.53	1.43	2.03
γ 89.0	2.12	1.46	1.39	1.96
γ 90.0	2.02	1.41	1.37	1.91
γ 91.0	1.96	1.38	1.33	1.85
γ 92.0	1.91	1.35	1.30	1.81
γ 93.0	1.87	1.31	1.28	1.77

IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	1.83	1.29	1.25	1.73
γ 95.0	1.79	1.25	1.22	1.69
γ 96.0	1.74	1.22	1.20	1.65
γ 97.0	1.70	1.20	1.18	1.63
γ 98.0	1.67	1.17	1.16	1.59
γ 99.0	1.64	1.15	1.14	1.56
γ 100.0	1.60	1.13	1.13	1.53
γ 101.0	1.57	1.11	1.11	1.50
γ 102.0	1.53	1.10	1.09	1.47
γ 103.0	1.51	1.07	1.07	1.45
γ 104.0	1.48	1.06	1.07	1.44
γ 105.0	1.46	1.04	1.05	1.42
γ 106.0	1.42	1.02	1.05	1.39
γ 107.0	1.39	1.00	1.04	1.38
γ 108.0	1.38	0.99	1.05	1.35
γ 109.0	1.35	0.98	1.04	1.34
γ 110.0	1.34	0.96	1.03	1.34
γ 111.0	1.31	0.95	1.04	1.32
γ 112.0	1.29	0.95	1.05	1.31
γ 113.0	1.28	0.94	1.05	1.31
γ 114.0	1.26	0.93	1.05	1.31
γ 115.0	1.26	0.93	1.06	1.31
γ 116.0	1.24	0.93	1.08	1.32
γ 117.0	1.24	0.94	1.09	1.32
γ 118.0	1.24	0.94	1.11	1.33
γ 119.0	1.22	0.95	1.13	1.34
γ 120.0	1.22	0.95	1.15	1.35
γ 121.0	1.23	0.97	1.18	1.38
γ 122.0	1.23	0.99	1.21	1.40
γ 123.0	1.25	1.01	1.24	1.42
γ 124.0	1.26	1.02	1.28	1.45
γ 125.0	1.27	1.06	1.33	1.49
γ 126.0	1.30	1.09	1.37	1.52
γ 127.0	1.32	1.11	1.42	1.57
γ 128.0	1.35	1.15	1.47	1.61
γ 129.0	1.39	1.20	1.53	1.66
γ 130.0	1.42	1.24	1.59	1.71
γ 131.0	1.47	1.29	1.66	1.76
γ 132.0	1.51	1.34	1.73	1.83
γ 133.0	1.56	1.40	1.80	1.88
γ 134.0	1.61	1.45	1.87	1.94
γ 135.0	1.66	1.52	1.93	2.01
γ 136.0	1.72	1.59	2.00	2.07
γ 137.0	1.79	1.66	2.07	2.14
γ 138.0	1.85	1.73	2.16	2.21
γ 139.0	1.92	1.80	2.24	2.28
γ 140.0	1.99	1.88	2.32	2.35

IES Indoor Report

Photometric Filename:MD10-06-XX-05 2700K RA90 38D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	2.05	1.96	2.40	2.42
γ 142.0	2.13	2.03	2.47	2.50
γ 143.0	2.21	2.11	2.56	2.57
γ 144.0	2.28	2.18	2.63	2.65
γ 145.0	2.36	2.26	2.71	2.71
γ 146.0	2.44	2.34	2.79	2.79
γ 147.0	2.51	2.40	2.86	2.86
γ 148.0	2.59	2.48	2.92	2.93
γ 149.0	2.67	2.56	3.00	2.99
γ 150.0	2.73	2.63	3.07	3.06
γ 151.0	2.81	2.71	3.12	3.12
γ 152.0	2.88	2.77	3.18	3.18
γ 153.0	2.95	2.84	3.24	3.23
γ 154.0	3.00	2.90	3.30	3.28
γ 155.0	3.08	2.96	3.35	3.33
γ 156.0	3.12	3.01	3.39	3.37
γ 157.0	3.20	3.08	3.44	3.41
γ 158.0	3.24	3.13	3.47	3.44
γ 159.0	3.29	3.17	3.50	3.49
γ 160.0	3.33	3.21	3.52	3.50
γ 161.0	3.38	3.24	3.54	3.52
γ 162.0	3.41	3.27	3.56	3.54
γ 163.0	3.43	3.31	3.57	3.55
γ 164.0	3.46	3.33	3.57	3.56
γ 165.0	3.49	3.34	3.58	3.56
γ 166.0	3.50	3.37	3.58	3.56
γ 167.0	3.52	3.38	3.60	3.57
γ 168.0	3.53	3.39	3.61	3.56
γ 169.0	3.54	3.41	3.61	3.57
γ 170.0	3.56	3.42	3.62	3.58
γ 171.0	3.57	3.44	3.62	3.58
γ 172.0	3.59	3.45	3.63	3.59
γ 173.0	3.60	3.47	3.64	3.60
γ 174.0	3.60	3.48	3.65	3.61
γ 175.0	3.62	3.50	3.65	3.62
γ 176.0	3.64	3.53	3.65	3.63
γ 177.0	3.65	3.54	3.67	3.64
γ 178.0	3.66	3.55	3.68	3.65
γ 179.0	3.68	3.56	3.68	3.65
γ 180.0	3.66	3.66	3.66	3.66