


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

| | |
|------------------------|---|
| Input Voltage/Hz | AC200-240V 50/60Hz |
| Output Voltage/Current | DC34V/130mA |
| Power | 6W |
| Rated Input Current | 0.03A |
| THD | <6% |
| PF value | >0.85 |
| Ingress Protection | IP40 |
| Operating Temperature | -10—40℃ |
| Dimmability | Triac dimmable with DIMMATE driver |

Optical Data

| | |
|--------------------------------|-------------------|
| LED Brand | Bridgelux COB LED |
| CRI | Ra> 80,Ra> 90 |
| Beam Angle | 38° |
| Colour temperatures | 2700K/3000K/4000K |
| System luminous efficacy up to | 105lm/W |

Packaging

| | |
|---------------------|------------------------------|
| Box Dimensions | L195 x W70 x H96 mm |
| Box Net Weight | 0.234Kg |
| Box Gross Weight | 0.291Kg |
| Carton Dimensions | L410 x W375 x H405 mm/40 PCS |
| Carton Net Weight | 9.36Kg |
| Carton Gross Weight | 11.64Kg |



| CCT | | Beam Angle | Lumen | Efficacy | | Beam Angle | Lumen | Efficacy |
|-------|-----|------------|-------|----------|-----|------------|-------|----------|
| 2700K | CRI | 38° | 555lm | 100lm/W | CRI | 38° | 459lm | 83lm/W |
| 3000K | | 38° | 556lm | 100lm/W | | 38° | 476lm | 86lm/W |
| 4000K | | 38° | 582lm | 105lm/W | | 38° | 502lm | 91lm/W |

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS