



Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.215Kg
Box Gross Weight	0.272Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	8.6Kg
Carton Gross Weight	10.88Kg

FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC12V/350mA
Power	5.5W
Rated Input Current	0.024A
THD	<25%
PF value	>0.85
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 90
Beam Angle	7°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	51.878lm/W



Model	CCT		Beam Angle	Lumen	Efficacy
MD10-06-XX-15	2700K	CRI 90+	7°	249.64lm	45.756lm/W
MD10-06-XX-15	3000K		7°	269.90lm	49.907lm/W
MD10-06-XX-15	4000K		7°	281.34lm	51.878lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS