


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

| | |
|------------------------|---|
| Input Voltage/Hz | AC200-240V 50/60Hz |
| Output Voltage/Current | DC12V/350mA |
| Power | 5.5W |
| Rated Input Current | 0.024A |
| THD | <25% |
| PF value | >0.85 |
| Ingress Protection | IP40 |
| Operating Temperature | -10–40°C |
| Dimmability | Triac dimmable with DIMMATE driver |

Optical Data

| | |
|--------------------------------|-------------------|
| LED Brand | Bridgelux COB LED |
| CRI | Ra > 90 |
| Beam Angle | 7° |
| Colour temperatures | 2700K/3000K/4000K |
| System luminous efficacy up to | 51.878lm/W |

Packaging

| | |
|---------------------|------------------------------|
| Box Dimensions | L195 x W70 x H96 mm |
| Box Net Weight | 0.215Kg |
| Box Gross Weight | 0.272Kg |
| Carton Dimensions | L410 x W375 x H405 mm/40 PCS |
| Carton Net Weight | 8.6Kg |
| Carton Gross Weight | 10.88Kg |



| Model | CCT | | Beam Angle | Lumen | Efficacy |
|---------------|-------|---------|------------|----------|------------|
| MD10-06-XX-15 | 2700K | CRI 90+ | 7° | 249.64lm | 45.756lm/W |
| MD10-06-XX-15 | 3000K | | 7° | 269.90lm | 49.907lm/W |
| MD10-06-XX-15 | 4000K | | 7° | 281.34lm | 51.878lm/W |

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Reuil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS