


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/210mA
Power	9W
Rated Input Current	0.045A
THD	<6%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80, Ra > 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	110lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.236Kg
Box Gross Weight	0.293Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	9.46Kg
Carton Gross Weight	11.72Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K		15°	978lm	106lm/W		15°	809lm	87lm/W
		25°	968lm	104lm/W		25°	801lm	86lm/W
		38°	978lm	105lm/W		38°	806lm	86lm/W
		60°	969lm	104lm/W		60°	799lm	86lm/W
3000K	CRI 80+	15°	904lm	96lm/W	CRI 90+	15°	806lm	90lm/W
		25°	970lm	104lm/W		25°	806lm	90lm/W
		38°	977lm	105lm/W		38°	800lm	90lm/W
		60°	972lm	104lm/W		60°	810lm	89lm/W
4000K		15°	1039lm	110lm/W		15°	871lm	94lm/W
		25°	1023lm	109lm/W		25°	876lm	93lm/W
		38°	1015lm	109lm/W		38°	866lm	93lm/W
		60°	1007lm	108lm/W		60°	863lm	96lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS