



Indoor Luminaire Photometric Data

Description Information

Luminary Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2019/11/19
Manufacture: Shenzhen Norming Lighting Co., Ltd	Shld.Ang(°):	Test Machine:GON-2000
Test Lab: QUality peatment	Frequency (Hz):	Lamp CCT(K): Ra:
Lum. Size (W*L*H): 0.050m*0.050m*0.060m	Lum. Area (m2): 0.005	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 810.260	Luminary Flux(lm): 810.258	Field Angle(10%Imax): 89.5(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 788.266lm 97.29%
Rated Voltage(V):	Luminary EER(lm/W): 89.839	Up Lumens&Percent: 21.992lm 2.71%
Tested Power(W): 9.019	Max. Candela(cd): 831.009	S/MH: C0_a180=0.810 C90_270=0.804
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf): 240.2, 0.041, 0.914	Beam Angle(50%Imax): 56.6(°)	ErP ϕ use(90°): 729.359lm
Lamp Size (W*L*H): 0.050m*0.050m*0.060m	Left=-28.5°, Right=28.1°	IRF(%): 234.901



2D Plane Light Intensity Distribution Curve

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19




IES Indoor Report

Photometric Filename:MD10-09-XX-02 3000K RA90 60D.IES

3D Light Intensity Distribution Modal

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.79	0.79	0.10	0.10	47.0-48.0	3.21	731.66	0.40	90.30
1.0-2.0	2.37	3.16	0.29	0.39	48.0-49.0	2.66	734.32	0.33	90.63
2.0-3.0	3.94	7.10	0.49	0.88	49.0-50.0	2.39	736.72	0.30	90.92
3.0-4.0	5.48	12.58	0.68	1.55	50.0-51.0	2.26	738.98	0.28	91.20
4.0-5.0	6.98	19.56	0.86	2.41	51.0-52.0	2.18	741.15	0.27	91.47
5.0-6.0	8.44	28.00	1.04	3.46	52.0-53.0	2.12	743.27	0.26	91.73
6.0-7.0	9.83	37.83	1.21	4.67	53.0-54.0	2.06	745.33	0.25	91.99
7.0-8.0	11.13	48.96	1.37	6.04	54.0-55.0	2.01	747.34	0.25	92.23
8.0-9.0	12.35	61.31	1.52	7.57	55.0-56.0	1.96	749.30	0.24	92.48
9.0-10.0	13.46	74.77	1.66	9.23	56.0-57.0	1.91	751.21	0.24	92.71
10.0-11.0	14.50	89.27	1.79	11.02	57.0-58.0	1.87	753.08	0.23	92.94
11.0-12.0	15.46	104.73	1.91	12.93	58.0-59.0	1.82	754.90	0.22	93.17
12.0-13.0	16.36	121.09	2.02	14.94	59.0-60.0	1.78	756.67	0.22	93.39
13.0-14.0	17.22	138.31	2.12	17.07	60.0-61.0	1.73	758.40	0.21	93.60
14.0-15.0	18.02	156.32	2.22	19.29	61.0-62.0	1.68	760.08	0.21	93.81
15.0-16.0	18.74	175.06	2.31	21.61	62.0-63.0	1.63	761.71	0.20	94.01
16.0-17.0	19.38	194.43	2.39	24.00	63.0-64.0	1.59	763.30	0.20	94.20
17.0-18.0	19.93	214.36	2.46	26.46	64.0-65.0	1.54	764.84	0.19	94.39
18.0-19.0	20.39	234.75	2.52	28.97	65.0-66.0	1.49	766.33	0.18	94.58
19.0-20.0	20.76	255.51	2.56	31.53	66.0-67.0	1.45	767.78	0.18	94.76
20.0-21.0	21.05	276.56	2.60	34.13	67.0-68.0	1.40	769.19	0.17	94.93
21.0-22.0	21.27	297.82	2.62	36.76	68.0-69.0	1.36	770.55	0.17	95.10
22.0-23.0	21.41	319.24	2.64	39.40	69.0-70.0	1.31	771.86	0.16	95.26
23.0-24.0	21.51	340.74	2.65	42.05	70.0-71.0	1.27	773.12	0.16	95.42
24.0-25.0	21.56	362.31	2.66	44.71	71.0-72.0	1.22	774.34	0.15	95.57
25.0-26.0	21.59	383.90	2.66	47.38	72.0-73.0	1.17	775.51	0.14	95.71
26.0-27.0	21.60	405.50	2.67	50.05	73.0-74.0	1.12	776.63	0.14	95.85
27.0-28.0	21.58	427.08	2.66	52.71	74.0-75.0	1.07	777.70	0.13	95.98
28.0-29.0	21.54	448.61	2.66	55.37	75.0-76.0	1.02	778.72	0.13	96.11
29.0-30.0	21.46	470.07	2.65	58.02	76.0-77.0	0.97	779.69	0.12	96.23
30.0-31.0	21.36	491.43	2.64	60.65	77.0-78.0	0.92	780.61	0.11	96.34
31.0-32.0	21.21	512.64	2.62	63.27	78.0-79.0	0.87	781.48	0.11	96.45
32.0-33.0	21.01	533.65	2.59	65.86	79.0-80.0	0.83	782.31	0.10	96.55
33.0-34.0	20.75	554.41	2.56	68.42	80.0-81.0	0.78	783.09	0.10	96.65
34.0-35.0	20.44	574.84	2.52	70.95	81.0-82.0	0.74	783.83	0.09	96.74
35.0-36.0	20.05	594.89	2.47	73.42	82.0-83.0	0.70	784.53	0.09	96.82
36.0-37.0	19.48	614.37	2.40	75.82	83.0-84.0	0.66	785.19	0.08	96.91
37.0-38.0	18.58	632.95	2.29	78.12	84.0-85.0	0.62	785.81	0.08	96.98
38.0-39.0	17.33	650.28	2.14	80.26	85.0-86.0	0.58	786.40	0.07	97.05
39.0-40.0	15.79	666.07	1.95	82.20	86.0-87.0	0.53	786.93	0.07	97.12
40.0-41.0	14.08	680.15	1.74	83.94	87.0-88.0	0.49	787.42	0.06	97.18
41.0-42.0	12.32	692.47	1.52	85.46	88.0-89.0	0.44	787.86	0.05	97.24
42.0-43.0	10.53	703.00	1.30	86.76	89.0-90.0	0.41	788.27	0.05	97.29
43.0-44.0	8.77	711.77	1.08	87.85	90.0-91.0	0.38	788.65	0.05	97.33
44.0-45.0	7.07	718.84	0.87	88.72	91.0-92.0	0.37	789.02	0.05	97.38
45.0-46.0	5.47	724.31	0.68	89.39	92.0-93.0	0.36	789.37	0.04	97.42
46.0-47.0	4.14	728.45	0.51	89.90	93.0-94.0	0.35	789.72	0.04	97.47

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.34	790.07	0.04	97.51	141.0-142.0	0.29	803.40	0.04	99.15
95.0-96.0	0.34	790.40	0.04	97.55	142.0-143.0	0.29	803.68	0.04	99.19
96.0-97.0	0.33	790.73	0.04	97.59	143.0-144.0	0.29	803.97	0.04	99.22
97.0-98.0	0.32	791.05	0.04	97.63	144.0-145.0	0.28	804.26	0.04	99.26
98.0-99.0	0.31	791.37	0.04	97.67	145.0-146.0	0.28	804.54	0.03	99.29
99.0-100.0	0.31	791.67	0.04	97.71	146.0-147.0	0.28	804.82	0.03	99.33
100.0-101.0	0.30	791.98	0.04	97.74	147.0-148.0	0.28	805.09	0.03	99.36
101.0-102.0	0.30	792.27	0.04	97.78	148.0-149.0	0.27	805.36	0.03	99.40
102.0-103.0	0.29	792.57	0.04	97.82	149.0-150.0	0.27	805.63	0.03	99.43
103.0-104.0	0.29	792.85	0.04	97.85	150.0-151.0	0.26	805.89	0.03	99.46
104.0-105.0	0.28	793.14	0.04	97.89	151.0-152.0	0.26	806.15	0.03	99.49
105.0-106.0	0.28	793.42	0.03	97.92	152.0-153.0	0.25	806.40	0.03	99.52
106.0-107.0	0.28	793.70	0.03	97.96	153.0-154.0	0.25	806.65	0.03	99.55
107.0-108.0	0.27	793.97	0.03	97.99	154.0-155.0	0.24	806.90	0.03	99.58
108.0-109.0	0.27	794.25	0.03	98.02	155.0-156.0	0.24	807.13	0.03	99.61
109.0-110.0	0.27	794.52	0.03	98.06	156.0-157.0	0.23	807.36	0.03	99.64
110.0-111.0	0.27	794.79	0.03	98.09	157.0-158.0	0.22	807.59	0.03	99.67
111.0-112.0	0.27	795.05	0.03	98.12	158.0-159.0	0.22	807.80	0.03	99.70
112.0-113.0	0.27	795.32	0.03	98.16	159.0-160.0	0.21	808.01	0.03	99.72
113.0-114.0	0.27	795.59	0.03	98.19	160.0-161.0	0.20	808.22	0.03	99.75
114.0-115.0	0.27	795.85	0.03	98.22	161.0-162.0	0.20	808.41	0.02	99.77
115.0-116.0	0.27	796.12	0.03	98.26	162.0-163.0	0.19	808.60	0.02	99.80
116.0-117.0	0.27	796.39	0.03	98.29	163.0-164.0	0.18	808.78	0.02	99.82
117.0-118.0	0.27	796.66	0.03	98.32	164.0-165.0	0.17	808.95	0.02	99.84
118.0-119.0	0.27	796.92	0.03	98.35	165.0-166.0	0.16	809.11	0.02	99.86
119.0-120.0	0.27	797.19	0.03	98.39	166.0-167.0	0.15	809.26	0.02	99.88
120.0-121.0	0.27	797.46	0.03	98.42	167.0-168.0	0.14	809.41	0.02	99.89
121.0-122.0	0.27	797.73	0.03	98.45	168.0-169.0	0.13	809.54	0.02	99.91
122.0-123.0	0.27	798.00	0.03	98.49	169.0-170.0	0.12	809.66	0.02	99.93
123.0-124.0	0.27	798.27	0.03	98.52	170.0-171.0	0.11	809.77	0.01	99.94
124.0-125.0	0.27	798.55	0.03	98.55	171.0-172.0	0.10	809.87	0.01	99.95
125.0-126.0	0.28	798.82	0.03	98.59	172.0-173.0	0.09	809.96	0.01	99.96
126.0-127.0	0.28	799.10	0.03	98.62	173.0-174.0	0.08	810.04	0.01	99.97
127.0-128.0	0.28	799.38	0.03	98.66	174.0-175.0	0.07	810.11	0.01	99.98
128.0-129.0	0.28	799.66	0.03	98.69	175.0-176.0	0.05	810.16	0.01	99.99
129.0-130.0	0.28	799.94	0.03	98.73	176.0-177.0	0.04	810.20	0.01	99.99
130.0-131.0	0.28	800.22	0.03	98.76	177.0-178.0	0.03	810.23	0.00	100.00
131.0-132.0	0.28	800.51	0.04	98.80	178.0-179.0	0.02	810.25	0.00	100.00
132.0-133.0	0.29	800.79	0.04	98.83	179.0-180.0	0.01	810.26	0.00	100.00
133.0-134.0	0.29	801.08	0.04	98.87					
134.0-135.0	0.29	801.37	0.04	98.90					
135.0-136.0	0.29	801.66	0.04	98.94					
136.0-137.0	0.29	801.95	0.04	98.97					
137.0-138.0	0.29	802.24	0.04	99.01					
138.0-139.0	0.29	802.53	0.04	99.05					
139.0-140.0	0.29	802.82	0.04	99.08					
140.0-141.0	0.29	803.11	0.04	99.12					

Rectangle ISO Lighting Intensity Diagram


Lum. Name:MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality peatment
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2019/11/19



Plane ISO-Illuminance Diagram

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 92.29

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
 View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

Space ISO Illuminance Curve



Curves:

[Unit: lx]

[EMax] =830.629

— [EMax*90%]=747.566

— [EMax*80%]=664.503

— [EMax*70%]=581.441

— [EMax*60%]=498.378

— [EMax*50%]=415.315

— [EMax*40%]=332.252

— [EMax*30%]=249.189

— [EMax*20%]=166.126

— [EMax*10%]=83.063

Space Plane Maximum Illuminance and @Angle:830.63lx,1.0deg

Plane Maximum Lighting Intensity and @Angle:831.009cd,0deg


IES Indoor Report

Photometric Filename:MD10-09-XX-02 3000K RA90 60D.IES

Illuminance-Distance Diagram

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

Illuminance-Distance Curve



IES Indoor Report

Photometric Filename:MD10-09-XX-02 3000K RA90 60D.IES

Indoor Luminance Limiting Curves

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E	a				2000	1000	500	≤ 300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	16511	7556	7231	6944	6680	6574	6599	7371	10616
C90	28986	8757	7416	7337	7140	7204	7512	8327	12513

Luminance Limiting Curve




Luminous Size: Length(m)=0.050 Width(m)=0.050 Height(m)=0.060 Area(m²)=0.005500
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: — C90-C270 Color: —

IES Indoor Report

Photometric Filename:MD10-09-XX-02 3000K RA90 60D.IES

Indoor Budgetary Estimate Table

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: MD10-09-XX-02 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/11/19

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	100	100	100	97
1	112	109	106	103	109	106	104	101	102	100	98	97	96	94	93	92	91	89
2	105	100	95	91	103	98	94	90	94	91	88	91	88	85	88	85	83	81
3	99	92	86	82	97	90	85	81	87	83	80	85	81	78	82	79	76	75
4	94	85	79	74	92	84	78	74	81	76	73	79	75	71	77	73	70	69
5	88	79	73	68	86	78	72	67	76	71	67	74	69	66	72	68	65	63
6	83	74	67	62	82	73	67	62	71	65	61	69	64	61	68	63	60	58
7	79	69	62	58	77	68	62	57	66	61	57	65	60	56	64	59	56	54
8	75	64	58	53	73	64	58	53	62	57	53	61	56	52	60	55	52	51
9	71	60	54	50	70	60	54	50	59	53	49	58	53	49	56	52	49	47
10	67	57	51	46	66	56	50	46	55	50	46	54	49	46	53	49	46	44

Unified Glare Rating Table

Table with 3 columns: Lum. Name, Lum. Catalog, Test ID; Lamp Name, Lamp Catalog, Test Lab; Manufacture, Test Machine, Test Date.

Unified Glare Rating Table

Table with 11 columns for room dimensions and UGR values. Includes sections for variations with observer position and reduced UGR table.

to the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	829.48	829.48	829.48	829.48
γ 1.0	831.01	824.76	830.94	823.48
γ 2.0	828.96	823.30	827.07	819.18
γ 3.0	824.73	822.42	824.03	812.94
γ 4.0	819.57	820.61	818.49	803.20
γ 5.0	811.78	815.93	812.48	791.38
γ 6.0	801.47	810.96	803.11	776.23
γ 7.0	788.54	802.52	791.60	757.96
γ 8.0	771.84	792.60	776.63	739.98
γ 9.0	753.04	779.02	759.86	720.57
γ 10.0	733.09	763.24	741.34	701.35
γ 11.0	713.37	745.50	722.56	683.32
γ 12.0	694.15	727.11	703.65	667.16
γ 13.0	676.21	709.45	686.83	650.27
γ 14.0	660.27	692.29	671.24	633.75
γ 15.0	644.19	675.91	654.92	616.54
γ 16.0	625.97	658.78	638.82	599.70
γ 17.0	608.73	641.74	621.34	581.95
γ 18.0	590.47	623.66	604.20	562.80
γ 19.0	572.05	604.94	585.34	544.07
γ 20.0	553.38	586.16	566.45	524.41
γ 21.0	534.21	567.21	547.43	505.05
γ 22.0	515.40	548.86	527.77	486.88
γ 23.0	496.55	529.42	508.24	468.89
γ 24.0	478.96	510.01	490.07	452.52
γ 25.0	462.15	491.98	471.67	436.25
γ 26.0	447.09	474.47	454.15	421.15
γ 27.0	431.47	457.43	438.06	407.23
γ 28.0	417.09	441.29	423.21	393.52
γ 29.0	403.34	426.08	408.49	379.49
γ 30.0	390.09	412.00	394.56	365.50
γ 31.0	377.31	398.12	380.72	351.90
γ 32.0	363.98	384.21	367.41	337.88
γ 33.0	350.81	370.51	354.11	323.52
γ 34.0	337.20	357.41	340.46	309.15
γ 35.0	323.49	344.37	325.63	294.74
γ 36.0	309.08	330.46	311.52	279.00
γ 37.0	289.76	314.73	295.54	259.13
γ 38.0	261.99	298.40	273.56	233.22
γ 39.0	231.82	277.61	246.84	207.02
γ 40.0	200.69	251.93	218.62	176.74
γ 41.0	168.69	224.64	190.58	150.07
γ 42.0	140.82	195.07	162.71	123.47
γ 43.0	112.58	165.85	137.92	99.13
γ 44.0	87.71	138.57	113.34	74.59
γ 45.0	64.21	112.73	90.21	54.06
γ 46.0	44.86	87.93	68.31	37.37

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	33.66	66.29	49.43	28.37
γ 48.0	28.90	48.50	36.96	25.22
γ 49.0	27.65	36.96	31.34	24.04
γ 50.0	26.71	30.96	29.02	23.07
γ 51.0	25.73	28.28	27.41	22.25
γ 52.0	24.89	26.75	25.94	21.67
γ 53.0	24.19	25.52	24.58	21.04
γ 54.0	23.50	24.42	23.35	20.38
γ 55.0	22.81	23.39	22.33	19.81
γ 56.0	22.06	22.67	21.25	19.19
γ 57.0	21.33	22.11	20.23	18.58
γ 58.0	20.61	21.46	19.26	17.93
γ 59.0	19.86	20.82	18.56	17.26
γ 60.0	19.09	20.18	17.91	16.64
γ 61.0	18.29	19.43	17.25	16.04
γ 62.0	17.61	18.70	16.58	15.46
γ 63.0	16.90	17.94	16.00	14.97
γ 64.0	16.24	17.25	15.53	14.37
γ 65.0	15.53	16.60	15.03	13.88
γ 66.0	14.88	15.99	14.50	13.42
γ 67.0	14.26	15.39	14.04	12.89
γ 68.0	13.58	14.73	13.60	12.44
γ 69.0	12.96	14.14	13.11	11.98
γ 70.0	12.37	13.55	12.66	11.49
γ 71.0	11.69	12.96	12.25	11.03
γ 72.0	11.11	12.36	11.75	10.55
γ 73.0	10.60	11.79	11.29	10.00
γ 74.0	10.00	11.17	10.82	9.49
γ 75.0	9.39	10.69	10.26	9.09
γ 76.0	8.89	10.12	9.73	8.65
γ 77.0	8.34	9.48	9.33	8.12
γ 78.0	7.75	9.00	8.95	7.72
γ 79.0	7.40	8.51	8.41	7.26
γ 80.0	7.04	7.95	7.99	6.76
γ 81.0	6.47	7.66	7.58	6.40
γ 82.0	6.06	7.24	7.07	6.10
γ 83.0	5.71	6.74	6.72	5.82
γ 84.0	5.41	6.32	6.41	5.47
γ 85.0	5.09	6.00	6.10	4.92
γ 86.0	4.68	5.71	5.55	4.51
γ 87.0	4.27	5.41	4.82	4.06
γ 88.0	4.02	4.91	4.10	3.90
γ 89.0	3.82	4.19	3.61	3.80
γ 90.0	3.71	3.57	3.31	3.71
γ 91.0	3.62	3.12	3.23	3.62
γ 92.0	3.53	3.03	3.15	3.53
γ 93.0	3.45	2.97	3.09	3.44

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	3.37	2.90	3.02	3.37
γ 95.0	3.30	2.84	2.95	3.30
γ 96.0	3.24	2.78	2.90	3.24
γ 97.0	3.17	2.72	2.84	3.18
γ 98.0	3.11	2.67	2.78	3.13
γ 99.0	3.06	2.62	2.74	3.09
γ 100.0	3.01	2.58	2.70	3.04
γ 101.0	2.95	2.53	2.66	2.99
γ 102.0	2.91	2.50	2.63	2.96
γ 103.0	2.88	2.46	2.60	2.92
γ 104.0	2.84	2.43	2.58	2.90
γ 105.0	2.81	2.41	2.56	2.88
γ 106.0	2.80	2.38	2.55	2.87
γ 107.0	2.77	2.37	2.53	2.86
γ 108.0	2.76	2.35	2.54	2.85
γ 109.0	2.76	2.35	2.53	2.85
γ 110.0	2.75	2.35	2.53	2.86
γ 111.0	2.74	2.35	2.55	2.86
γ 112.0	2.76	2.35	2.56	2.87
γ 113.0	2.77	2.36	2.58	2.88
γ 114.0	2.77	2.37	2.60	2.90
γ 115.0	2.79	2.39	2.62	2.93
γ 116.0	2.80	2.41	2.66	2.94
γ 117.0	2.83	2.44	2.69	2.98
γ 118.0	2.85	2.46	2.71	3.01
γ 119.0	2.87	2.49	2.76	3.04
γ 120.0	2.91	2.53	2.79	3.09
γ 121.0	2.95	2.56	2.84	3.12
γ 122.0	2.98	2.60	2.89	3.17
γ 123.0	3.02	2.65	2.94	3.21
γ 124.0	3.08	2.69	2.99	3.26
γ 125.0	3.13	2.75	3.05	3.32
γ 126.0	3.18	2.80	3.10	3.38
γ 127.0	3.23	2.85	3.16	3.43
γ 128.0	3.29	2.91	3.23	3.49
γ 129.0	3.35	2.97	3.29	3.56
γ 130.0	3.41	3.03	3.36	3.63
γ 131.0	3.48	3.10	3.43	3.69
γ 132.0	3.55	3.16	3.52	3.77
γ 133.0	3.63	3.23	3.59	3.84
γ 134.0	3.69	3.31	3.66	3.90
γ 135.0	3.77	3.38	3.75	3.97
γ 136.0	3.85	3.47	3.83	4.06
γ 137.0	3.92	3.54	3.91	4.13
γ 138.0	4.01	3.63	3.99	4.20
γ 139.0	4.08	3.70	4.07	4.29
γ 140.0	4.15	3.80	4.16	4.35

IES Indoor Report

Photometric Filename:MD10-09-XX-02 3000K RA90 60D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	4.23	3.88	4.24	4.43
γ 142.0	4.31	3.96	4.32	4.50
γ 143.0	4.38	4.04	4.41	4.57
γ 144.0	4.46	4.12	4.49	4.64
γ 145.0	4.53	4.19	4.57	4.72
γ 146.0	4.59	4.27	4.64	4.78
γ 147.0	4.66	4.34	4.70	4.84
γ 148.0	4.73	4.42	4.78	4.90
γ 149.0	4.79	4.49	4.85	4.96
γ 150.0	4.86	4.57	4.91	5.01
γ 151.0	4.92	4.64	4.98	5.08
γ 152.0	4.99	4.70	5.04	5.14
γ 153.0	5.06	4.78	5.11	5.20
γ 154.0	5.13	4.84	5.17	5.26
γ 155.0	5.20	4.91	5.25	5.33
γ 156.0	5.27	4.99	5.31	5.39
γ 157.0	5.34	5.06	5.39	5.45
γ 158.0	5.40	5.14	5.46	5.51
γ 159.0	5.48	5.21	5.53	5.58
γ 160.0	5.54	5.29	5.60	5.64
γ 161.0	5.62	5.36	5.66	5.69
γ 162.0	5.69	5.44	5.73	5.75
γ 163.0	5.75	5.50	5.80	5.81
γ 164.0	5.81	5.59	5.86	5.87
γ 165.0	5.88	5.65	5.92	5.92
γ 166.0	5.94	5.71	5.98	5.97
γ 167.0	5.99	5.78	6.03	6.02
γ 168.0	6.06	5.86	6.10	6.08
γ 169.0	6.11	5.90	6.15	6.12
γ 170.0	6.17	5.96	6.20	6.17
γ 171.0	6.22	6.02	6.26	6.22
γ 172.0	6.26	6.07	6.30	6.24
γ 173.0	6.32	6.12	6.35	6.29
γ 174.0	6.36	6.17	6.39	6.32
γ 175.0	6.40	6.22	6.43	6.35
γ 176.0	6.43	6.27	6.46	6.37
γ 177.0	6.45	6.30	6.48	6.40
γ 178.0	6.49	6.32	6.52	6.41
γ 179.0	6.49	6.36	6.53	6.42
γ 180.0	6.47	6.47	6.47	6.47