


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- External driver with DALI dimming.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/230mA
Power	10W
Rated Input Current	0.05mA
THD	<20%
PF value	>0.95
Ingress Protection	IP40
Operating Temperature	-10-40°C
Dimmability	ACTEC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 80, Ra > 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	113.1lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.284Kg
Box Gross Weight	0.350Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	11.36Kg
Carton Gross Weight	17.40Kg



CCT	Beam Angle			Lumen	Efficacy	Beam Angle			Lumen	Efficacy
2700K	CRI 80+	15°	825lm	81.4lm/W	CRI 90+	15°	753lm	74.1lm/W		
		25°	925lm	91.7lm/W		25°	804lm	79.1lm/W		
		38°	928lm	92lm/W		38°	808lm	79.6lm/W		
		60°	913lm	90.7lm/W		60°	808lm	79lm/W		
3000K		15°	1036lm	101lm/W		15°	889lm	88lm/W		
		25°	1036lm	100.8lm/W		25°	879lm	86lm/W		
		38°	1029lm	100.4lm/W		38°	867lm	85.7lm/W		
		60°	1023lm	99.8lm/W		60°	873lm	85.6lm/W		
4000K		15°	1148lm	113.1lm/W		15°	909lm	90lm/W		
		25°	1115lm	110lm/W		25°	907lm	89.7lm/W		
		38°	1107lm	109lm/W		38°	903lm	89.3lm/W		
		60°	1093lm	107.7lm/W		60°	989lm	88.9lm/W		

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS