


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/210mA
Power	9W
Rated Input Current	0.045A
THD	<6%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80, Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	112lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.235Kg
Box Gross Weight	0.291Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	9.50Kg
Carton Gross Weight	11.64Kg



CCT		Beam Angle	Lumen	Efficacy	Beam Angle		Lumen	Efficacy
2700K	CRI 80+	15°	928lm	100lm/W	CRI 90+	15°	744lm	80lm/W
		24°	966lm	104lm/W		24°	762lm	82lm/W
		36°	977lm	105lm/W		36°	814lm	87lm/W
		60°	992lm	107lm/W		60°	842lm	88lm/W
3000K		15°	907lm	98lm/W		15°	771lm	83lm/W
		24°	930lm	100lm/W		24°	832lm	89lm/W
		36°	987lm	105lm/W		36°	836lm	90lm/W
		60°	1006lm	107lm/W		60°	845lm	90lm/W
4000K		15°	988lm	105lm/W		15°	808lm	87lm/W
		24°	996lm	107lm/W		24°	840lm	91lm/W
		36°	1048lm	112lm/W		36°	894lm	97lm/W
		60°	1042lm	110lm/W		60°	912lm	99lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS