


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/210mA
Power	9W
Rated Input Current	0.045A
THD	<6%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>80, Ra>90
Beam Angle	18°/24°/38°/50°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	111lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.256Kg
Box Gross Weight	0.313Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	10.25Kg
Carton Gross Weight	13.72Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	18°	927lm	99lm/W	CRI 90+	18°	746lm	81lm/W
		24°	948lm	102lm/W		24°	776lm	85lm/W
		38°	951lm	102lm/W		38°	768lm	84lm/W
		50°	904lm	97lm/W		50°	738lm	81lm/W
18°		948lm	102lm/W	18°		806lm	87lm/W	
24°		971lm	104lm/W	24°		828lm	90lm/W	
38°		974lm	105lm/W	38°		825lm	89lm/W	
50°		927lm	100lm/W	50°		793lm	86lm/W	
4000K		18°	1000lm	107lm/W		18°	859lm	94lm/W
		24°	1026lm	110lm/W		24°	880lm	96lm/W
		38°	1030lm	111lm/W		38°	880lm	96lm/W
		50°	983lm	106lm/W		50°	847lm	92lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS