


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/210mA
Power	9W
Rated Input Current	0.045A
THD	<6%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
Beam Angle	18°/30°/50°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	91lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.262Kg
Box Gross Weight	0.319Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	10.48Kg
Carton Gross Weight	13.96Kg



CCT		Beam Angle	Lumen	Efficacy
2700K	CRI 90+	18°	558lm	60lm/W
		30°	742lm	80lm/W
		50°	750lm	81lm/W
3000K		18°	534lm	57lm/W
		30°	710lm	76lm/W
		50°	719lm	77lm/W
4000K		18°	622lm	67lm/W
		30°	823lm	89lm/W
		50°	837lm	91lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS