


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 92.73 lm/W
MODEL		I _{max} (cd)	2158	S/MH(C0/180)	0.59	
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	0.58	
RATED VOLTAGE(V)	240	TOTAL FLUX(lm)	925.64	η UP,DN(C0-180)	0.0,48.8	
NOMINAL FLUX(lm)	925.644	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.2	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50	
TEST VOLTAGE(V)	240.38	η down (%)	100.0	CIBSE SHR MAX	0.60	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1781	1785	1789	1814	1837	1839	1829	1796	0- 10	190.2	190.2	20.5,20.5
20	816.7	829.4	829.8	864.0	897.3	898.2	863.0	817.3	10- 20	363.6	553.8	59.8,59.8
30	237.4	238.9	236.4	253.9	282.8	283.6	258.9	234.4	20- 30	225.0	778.7	84.1,84.1
40	63.86	64.17	64.96	72.03	81.27	82.83	74.22	65.00	30- 40	86.85	865.6	93.5,93.5
50	24.94	25.21	25.88	27.70	29.60	31.00	28.76	26.10	40- 50	34.18	899.8	97.2,97.2
60	11.63	11.53	11.56	11.98	12.44	12.83	12.75	12.10	50- 60	16.73	916.5	99,99
70	3.814	3.576	3.501	3.771	4.151	3.989	4.086	3.806	60- 70	7.437	923.9	99.8,99.8
80	0.3403	0.3135	0.3117	0.3149	0.3538	0.2868	0.2341	0.2608	70- 80	1.604	925.5	100,100
90	0.0077	0	0.0106	0	0.0003	0	0.0029	0	80- 90	0.1068	925.6	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 885.95 lm

%lum = 95.7%

%lamp = 95.7%

Conical surface Flux(130deg): 921.18 lm

%lum = 99.5%


%lamp = 99.5%

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
 Humidity:65.0%
 Test Distance:3.090m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1379	94
80	1511	1379
75	4301	3096
70	8595	7864
65	12976	12533
60	17930	17756
55	22791	23282
50	29905	30931
45	41682	43151


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
 Humidity:65.0%
 Test Distance:3.090m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.161	.092	.029	.154	.088	.028	.142	.081	.026	.130	.075	.024	.120	.069	.022		
2.0	.152	.083	.026	.147	.081	.025	.136	.076	.024	.127	.071	.022	.118	.067	.021		
3.0	.144	.077	.023	.139	.075	.022	.130	.071	.021	.122	.067	.021	.115	.063	.020		
4.0	.136	.071	.021	.132	.069	.020	.124	.066	.020	.117	.063	.019	.111	.060	.018		
5.0	.129	.066	.019	.125	.064	.019	.119	.062	.018	.113	.060	.018	.107	.057	.017		
6.0	.122	.061	.018	.119	.060	.017	.114	.058	.017	.108	.056	.017	.104	.054	.016		
7.0	.117	.058	.016	.114	.057	.016	.109	.055	.016	.104	.053	.016	.100	.052	.015		
8.0	.111	.054	.015	.109	.054	.015	.105	.052	.015	.100	.051	.015	.097	.050	.014		
9.0	.107	.052	.014	.104	.051	.014	.101	.050	.014	.097	.049	.014	.093	.047	.014		
10.0	.102	.049	.014	.100	.048	.014	.097	.047	.013	.093	.046	.013	.090	.045	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.170	.157	.146	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016		
2.0	.154	.133	.115	.132	.114	.099	.090	.079	.069	.052	.046	.041	.017	.015	.013		
3.0	.140	.113	.092	.120	.098	.080	.083	.068	.056	.048	.040	.033	.015	.013	.011		
4.0	.129	.098	.075	.111	.085	.065	.076	.059	.046	.044	.035	.027	.014	.011	.009		
5.0	.119	.087	.062	.103	.075	.054	.071	.052	.038	.041	.031	.023	.013	.010	.007		
6.0	.111	.077	.052	.096	.067	.046	.066	.047	.032	.038	.027	.019	.012	.009	.006		
7.0	.104	.069	.044	.090	.060	.039	.062	.042	.027	.036	.025	.016	.012	.008	.005		
8.0	.098	.063	.038	.085	.054	.033	.059	.038	.024	.034	.023	.014	.011	.007	.005		
9.0	.093	.057	.033	.080	.050	.029	.055	.035	.021	.032	.021	.012	.010	.007	.004		
10.0	.088	.053	.029	.076	.046	.025	.053	.032	.018	.031	.019	.011	.010	.006	.004		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm										
NAME: MD10-10-XX-01 3000K RA90 36D					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.: Norming Lighting					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.8	19.6	19.0	19.8	19.9	18.8	19.7	19.0	19.8	20.0
3H	18.9	19.6	19.1	19.8	20.0	18.9	19.6	19.1	19.8	20.0
4H	18.8	19.5	19.1	19.8	20.0	18.8	19.5	19.1	19.8	20.0
6H	18.7	19.4	19.0	19.7	19.9	18.7	19.4	19.0	19.6	19.9
8H	18.7	19.3	19.0	19.6	19.9	18.7	19.3	19.0	19.6	19.8
12H	18.7	19.3	19.0	19.5	19.8	18.6	19.3	19.0	19.5	19.8
4H 2H	18.8	19.5	19.0	19.7	19.9	18.8	19.5	19.1	19.7	20.0
3H	18.9	19.5	19.2	19.8	20.0	18.9	19.5	19.2	19.8	20.0
4H	18.8	19.4	19.2	19.7	20.0	18.8	19.4	19.2	19.7	20.0
6H	18.7	19.2	19.1	19.6	19.9	18.7	19.2	19.1	19.6	19.9
8H	18.7	19.2	19.1	19.5	19.9	18.7	19.1	19.1	19.5	19.9
12H	18.6	19.1	19.0	19.4	19.8	18.6	19.0	19.0	19.4	19.8
8H 4H	18.7	19.2	19.1	19.5	19.9	18.7	19.2	19.1	19.5	19.9
6H	18.6	19.0	19.0	19.4	19.8	18.6	19.0	19.0	19.4	19.8
8H	18.6	18.9	19.0	19.3	19.7	18.5	18.9	19.0	19.3	19.7
12H	18.5	18.8	19.0	19.2	19.7	18.5	18.8	18.9	19.2	19.7
12H 4H	18.6	19.1	19.1	19.4	19.8	18.6	19.1	19.0	19.4	19.8
6H	18.5	18.9	19.0	19.3	19.7	18.5	18.9	19.0	19.3	19.7
8H	18.5	18.8	19.0	19.2	19.7	18.5	18.8	18.9	19.2	19.7
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 2.0 / - 2.9					+ 2.0 / - 2.9				
1.5H	+ 3.1 / - 1.9					+ 3.1 / - 2.0				
2.0H	+ 2.6 / - 2.2					+ 2.8 / - 2.4				

CIE Pub.117, 925.6 lm Total Lamp Luminous Flux Corrected (8log(F/F0) = -0.3)
Area: 0.0013 m2

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	87	81	77	86	81	77	74
0.80	95	89	85	94	89	85	93	88	85	81
1.00	99	94	90	98	93	90	97	93	89	85
1.25	103	98	95	102	98	94	100	96	93	89
1.50	106	101	98	105	101	97	103	99	96	92
2.00	109	104	101	107	103	101	105	101	99	94
2.50	110	107	104	109	105	103	106	103	101	95
3.00	112	108	106	110	107	105	107	104	102	96
4.00	114	111	109	112	110	108	108	106	105	98
5.00	115	113	111	113	111	109	109	108	106	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:240.5V I:0.0446A P:10.0W PF:0.9316 Freq:49.99Hz		
UTHDi:0.16% ITHDi:20.60% KDisp:0.9484 Lamp Flux:925.644x1 lm		
NAME: MD10-10-XX-01 3000K RA90 36D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	13403
L_0~180 (75) av	4138
L_0~180 (85) av	1415
L_90~270 (65) av	13369
L_90~270 (75) av	2880
L_90~270 (85) av	56
L_45 (65) av	13243
L_45 (75) av	3799
L_45 (85) av	194

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

```