


## FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- External driver with DALI dimming.
- 5-year guarantee.



## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/230mA
Power	10W
Rated Input Current	0.05A
THD	<25%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	ACTEC DALI

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	118lm/W

## Packaging

Box Dimensions	L208 x W80 x H106 mm
Box Net Weight	0.284Kg
Box Gross Weight	0.350Kg
Carton Dimensions	L430 x W415 x H450 mm/40 PCS
Carton Net Weight	11.36Kg
Carton Gross Weight	17.40Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	889lm	88lm/W	CRI 90+	15°	778lm	76lm/W
		24°	888lm	88lm/W		24°	785lm	77lm/W
		36°	939lm	93lm/W		36°	817lm	80lm/W
		60°	913lm	90lm/W		60°	793lm	77lm/W
3000K		15°	1062lm	100lm/W		15°	845lm	83lm/W
		24°	1071lm	104lm/W		24°	849lm	84lm/W
		36°	1046lm	101lm/W		36°	871lm	86lm/W
		60°	1024lm	99.8lm/W		60°	872lm	86lm/W
4000K		15°	1228lm	118lm/W		15°	987lm	97lm/W
		24°	1220lm	118lm/W		24°	1008lm	99lm/W
		36°	1173lm	113lm/W		36°	907lm	89lm/W
		60°	1131lm	109lm/W		60°	894lm	88lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS