



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/230mA
Power	10W
Rated Input Current	0.055A
THD	<25%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	116lm/W

Packaging

Box Dimensions	L208 x W80 x H106 mm
Box Net Weight	0.257Kg
Box Gross Weight	0.313Kg
Carton Dimensions	L430 x W415 x H450 mm/40 PCS
Carton Net Weight	10.28Kg
Carton Gross Weight	12.53Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1099lm	110lm/W	CRI 90+	15°	901lm	89lm/W
		24°	1087lm	109lm/W		24°	900lm	89lm/W
		36°	1087lm	109lm/W		36°	895lm	89lm/W
		60°	1045lm	105lm/W		60°	864lm	85lm/W
3000K		15°	1171lm	116lm/W		15°	929lm	93lm/W
		24°	1168lm	115lm/W		24°	931lm	93lm/W
		36°	1163lm	115lm/W		36°	926lm	93lm/W
		60°	1122lm	111lm/W		60°	893lm	89lm/W
4000K		15°	1150lm	114lm/W		15°	975lm	98lm/W
		24°	1151lm	114lm/W		24°	974lm	98lm/W
		36°	1143lm	113lm/W		36°	968lm	97lm/W
		60°	1101lm	109lm/W		60°	933lm	94lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS