



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/230mA
Power	10W
Rated Input Current	0.055A
THD	<25%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80, Ra> 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	112lm/W

Packaging

Box Dimensions	L208 x W80 x H106 mm
Box Net Weight	0.248Kg
Box Gross Weight	0.304Kg
Carton Dimensions	L430 x W415 x H450 mm/40 PCS
Carton Net Weight	9.92Kg
Carton Gross Weight	12.16Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1079lm	107lm/W	CRI 90+	15°	870lm	87lm/W
		25°	1072lm	107lm/W		25°	876lm	87lm/W
		38°	1067lm	107lm/W		38°	875lm	87lm/W
		60°	1062lm	106lm/W		60°	873lm	87lm/W
3000K		15°	1123lm	111lm/W		15°	900lm	90lm/W
		25°	1130lm	112lm/W		25°	907lm	91lm/W
		38°	1128lm	111lm/W		38°	905lm	91lm/W
		60°	1127lm	111lm/W		60°	904lm	90lm/W
4000K		15°	1104lm	109lm/W		15°	934lm	94lm/W
		25°	1111lm	110lm/W		25°	941lm	95lm/W
		38°	1106lm	110lm/W		38°	935lm	94lm/W
		60°	1106lm	110lm/W		60°	938lm	94lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS