


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 96.51 lm/W
MODEL		Imax (cd)	4153	S/MH(C0/180)	0.36	
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	0.38	
RATED VOLTAGE(V)	240	TOTAL FLUX(lm)	958.70	η UP,DN(C0-180)	0.0,50.0	
NOMINAL FLUX(lm)	958.7	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.0	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE(V)	240.35	η down (%)	100.0	CIBSE SHR MAX	0.30	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2421	2345	2247	2223	2236	2291	2404	2434	0- 10	304.1	304.1	31.7,31.7
20	627.1	619.9	598.5	605.1	602.3	614.9	627.8	627.9	10- 20	325.8	629.9	65.7,65.7
30	232.9	231.4	229.4	227.8	227.7	225.6	233.1	228.4	20- 30	175.4	805.4	84,84
40	82.01	83.29	81.88	79.72	78.45	78.69	81.83	79.65	30- 40	87.78	893.1	93.2,93.2
50	29.26	30.42	29.24	27.17	25.58	27.00	28.91	28.70	40- 50	37.83	931.0	97.1,97.1
60	11.18	12.30	11.39	10.61	10.02	11.01	11.39	11.37	50- 60	16.34	947.3	98.8,98.8
70	4.844	5.331	5.154	5.072	4.908	5.312	5.261	5.086	60- 70	7.565	954.9	99.6,99.6
80	1.508	1.659	1.608	1.770	1.770	1.297	0.7578	0.9842	70- 80	3.481	958.3	100,100
90	0.0186	0.0051	0.0231	0.0045	0.0083	0.0061	0.0119	0.0052	80- 90	0.3513	958.7	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 916.18 lm

%lum = 95.6%

%lamp = 95.6%

Conical surface Flux(130deg): 951.73 lm

%lum = 99.3%


%lamp = 99.3%

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
 Humidity:65.0%
 Test Distance:3.090m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	2129	295
80	6690	7121
75	9442	9920
70	10914	11585
65	12913	13706
60	17224	17506
55	24323	24315
50	35074	34973
45	52510	52233


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.154	.088	.028	.147	.084	.027	.135	.077	.025	.123	.071	.023	.113	.065	.021		
2.0	.145	.079	.024	.139	.077	.024	.129	.072	.022	.119	.067	.021	.111	.063	.020		
3.0	.136	.072	.022	.131	.070	.021	.123	.066	.020	.115	.063	.019	.107	.059	.018		
4.0	.128	.067	.020	.124	.065	.019	.117	.062	.018	.110	.059	.018	.103	.056	.017		
5.0	.121	.062	.018	.117	.060	.018	.111	.058	.017	.105	.055	.016	.099	.053	.016		
6.0	.114	.057	.016	.111	.056	.016	.106	.054	.016	.101	.052	.015	.096	.050	.015		
7.0	.108	.054	.015	.106	.053	.015	.101	.051	.015	.097	.049	.014	.092	.048	.014		
8.0	.103	.050	.014	.101	.050	.014	.097	.048	.014	.093	.047	.014	.089	.046	.013		
9.0	.098	.048	.013	.096	.047	.013	.093	.046	.013	.089	.045	.013	.086	.044	.013		
10.0	.094	.045	.013	.092	.045	.012	.089	.044	.012	.086	.043	.012	.083	.042	.012		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.170	.158	.147	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016		
2.0	.153	.133	.116	.131	.114	.100	.090	.079	.070	.052	.046	.041	.017	.015	.013		
3.0	.139	.113	.093	.119	.098	.081	.082	.068	.057	.047	.040	.033	.015	.013	.011		
4.0	.127	.098	.076	.109	.085	.066	.075	.059	.047	.043	.035	.028	.014	.011	.009		
5.0	.117	.086	.063	.101	.075	.055	.069	.052	.039	.040	.031	.023	.013	.010	.008		
6.0	.109	.076	.053	.093	.066	.047	.064	.046	.033	.037	.027	.020	.012	.009	.006		
7.0	.101	.069	.046	.087	.059	.040	.060	.042	.028	.035	.025	.017	.011	.008	.006		
8.0	.095	.062	.039	.082	.054	.034	.057	.038	.024	.033	.022	.014	.011	.007	.005		
9.0	.089	.056	.034	.077	.049	.030	.053	.034	.021	.031	.020	.013	.010	.007	.004		
10.0	.084	.052	.030	.073	.045	.026	.051	.032	.019	.029	.019	.011	.010	.006	.004		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm										
NAME: MD10-10-XX-03 4000K RA90 24D					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.: Norming Lighting					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.6	20.4	19.8	20.5	20.7	19.6	20.4	19.8	20.5	20.7
3H	19.7	20.4	19.9	20.6	20.8	19.7	20.4	20.0	20.6	20.8
4H	19.7	20.4	20.0	20.6	20.8	19.8	20.4	20.0	20.6	20.8
6H	19.7	20.3	20.0	20.6	20.8	19.7	20.4	20.0	20.6	20.9
8H	19.7	20.3	20.0	20.5	20.8	19.7	20.3	20.0	20.6	20.8
12H	19.6	20.2	20.0	20.5	20.8	19.7	20.3	20.0	20.5	20.8
4H 2H	19.6	20.3	19.8	20.5	20.7	19.6	20.2	19.8	20.5	20.7
3H	19.7	20.3	20.0	20.6	20.9	19.8	20.3	20.1	20.6	20.9
4H	19.8	20.3	20.1	20.6	20.9	19.8	20.4	20.2	20.7	21.0
6H	19.8	20.3	20.2	20.6	21.0	19.9	20.3	20.2	20.7	21.0
8H	19.8	20.2	20.2	20.6	20.9	19.8	20.3	20.2	20.6	21.0
12H	19.7	20.1	20.1	20.5	20.9	19.8	20.2	20.2	20.5	20.9
8H 4H	19.7	20.2	20.1	20.5	20.9	19.8	20.2	20.2	20.6	20.9
6H	19.8	20.2	20.2	20.5	21.0	19.8	20.2	20.3	20.6	21.0
8H	19.8	20.1	20.2	20.5	20.9	19.8	20.1	20.2	20.5	21.0
12H	19.7	20.0	20.2	20.4	20.9	19.7	20.0	20.2	20.5	20.9
12H 4H	19.7	20.1	20.1	20.5	20.9	19.7	20.1	20.1	20.5	20.9
6H	19.7	20.1	20.2	20.5	20.9	19.8	20.1	20.2	20.5	21.0
8H	19.7	20.0	20.2	20.4	20.9	19.8	20.0	20.2	20.5	20.9
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 1.7 / - 2.8					+ 1.7 / - 2.7				
1.5H	+ 2.8 / - 2.1					+ 2.8 / - 2.1				
2.0H	+ 2.9 / - 2.3					+ 2.9 / - 2.2				

CIE Pub.117, 958.7 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = -0.1$)
Area: 0.0013 m²

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	87	81	77	86	80	77	73
0.80	95	89	85	94	88	85	93	88	85	81
1.00	99	94	90	98	93	90	97	93	89	85
1.25	103	98	94	102	97	94	100	96	93	89
1.50	106	101	98	105	100	97	102	99	96	92
2.00	109	104	101	107	103	100	104	101	99	94
2.50	110	106	103	109	105	102	105	103	101	95
3.00	112	108	106	110	107	105	107	104	102	96
4.00	114	111	109	112	109	107	108	106	105	98
5.00	115	113	111	113	111	109	109	108	106	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-14

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:240.4V I:0.0444A P:9.9W PF:0.9306 Freq:49.99Hz		
UTHDi:0.24% ITHDi:19.67% KDisp:0.9496 Lamp Flux:958.7x1 lm		
NAME: MD10-10-XX-03 4000K RA90 24D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Norming Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	12790
L_0~180 (75) av	9543
L_0~180 (85) av	2519
L_90~270 (65) av	13790
L_90~270 (75) av	9941
L_90~270 (85) av	211
L_45 (65) av	13709
L_45 (75) av	10093
L_45 (85) av	231

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
 Humidity:65.0%
 Test Distance:3.090m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-14

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.453
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

```