


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/230mA
Power	10W
Rated Input Current	0.055A
THD	<25%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	38°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	100lm/W

Packaging

Box Dimensions	L208 x W80 x H106 mm
Box Net Weight	0.271Kg
Box Gross Weight	0.328Kg
Carton Dimensions	L430 x W415 x H450 mm/40 PCS
Carton Net Weight	10.84Kg
Carton Gross Weight	13.12Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI	38°	931lm	93lm/W	CRI	38°	764lm	76lm/W
3000K		38°	1008lm	100lm/W		38°	811lm	81lm/W
4000K		38°	977lm	97lm/W		38°	841lm	85lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS