



## FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- External driver with DALI dimming.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/300mA
Power	13W
Rated Input Current	0.065A
THD	<20%
PF value	>0.95
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	ACTEC DALI

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 95
Beam Angle	15°/24°/36°/60°
Colour temperatures	2000K-3000K
System luminous efficacy up to	71.1lm/W

## Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.358Kg
Box Gross Weight	0.414Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	14.32Kg
Carton Gross Weight	18.82Kg



CCT	Beam Angle	Lumen	Efficacy
2000K-300K	15°	856lm	67.4lm/W
	24°	892lm	71.1lm/W
	36°	870lm	69.5lm/W
	60°	860lm	68.6lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS