



FEATURES


- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/300mA
Power	13W
Rated Input Current	0.065A
THD	<15%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>95
Beam Angle	24°/36°
Colour temperatures	2000K-3000K
System luminous efficacy up to	64lm/W



Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.314Kg
Box Gross Weight	0.370Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	12.54Kg
Carton Gross Weight	14.8Kg

CCT		Beam Angle	Lumen	Efficacy
2000K-3000K	CRI	24°	782lm	63lm/W
	95+	36°	800lm	64lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS