



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/300mA
Power	13W
Rated Input Current	0.065A
THD	<20%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Sunlike COB LED
CRI	Ra > 95
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	76lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.286Kg
Box Gross Weight	0.343Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	11.44Kg
Carton Gross Weight	13.7Kg



Model	CCT		Beam Angle	Lumen	Efficacy
MD10-13-SL-03	2700K	CRI 97+	15°	874lm	67lm/W
			24°	892lm	69lm/W
			36°	893lm	69lm/W
			60°	909lm	70lm/W
MD10-13-SL-03	3000K		15°	931lm	70lm/W
			24°	935lm	72lm/W
			36°	925lm	71lm/W
			60°	935lm	72lm/W
MD10-13-SL-03	4000K		15°	947lm	73lm/W
			24°	973lm	75lm/W
			36°	973lm	75lm/W
			60°	986lm	76lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS